

Be Your Window To The World



Picture and logos

SELLING POINTS

- Promień krzywizny 1500R oferuje najbardziej wciągające, wizualne wrażenia związane z patrzeniem na ekran podczas pracy i rozrywki.
- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie oczu
- Technologie Less Blue Light i Anti-Flicker chronią Twój wzrok przed zmęczeniem i znużeniem.
- Ergonomiczna aplikacja, Display Kit, oferuje niezwykle wygodne narzędzia, odpowiednią regulację barw i różne tryby wyświetlania tak, aby pomóc Ci w codziennej pracy
- 75-hercowa częstotliwość odświeżania oferuje znacznie lepsze wizualne wrażenia
- Duża elastyczność związaną z możliwością podłączenia do monitora różnych źródeł sygnału za pośrednictwem portu HDMI™ i złącza D-Sub (VGA)
- Zgodność ze standardem montażowym VESA
- Możliwość szybkiego dołączenia do telekonferencji z wykorzystaniem wbudowanych w monitor głośników



1. 1x HDMI™ (1.4b)
2. 1x D-Sub (VGA)
3. 1x Headphone-out
4. 1x Kensington Lock
5. 5x OSD Button

SPECIFICATION

| | | |
|--|---|-------------------------|
| Power | Power Type | Power Cable |
| Design | Adjustment (Tilt) | -3.5° ~ 21.5° |
| | VESA Mounting | 100x100mm |
| | Frameless Design | Yes |
| Dimension&Weight | Inside Carton Dimension (WxDxH) (mm) | 684 x 156 x 474 |
| | Inside Carton Dimension (WxDxH) (inch) | 26.93 x 6.14 x 18.66 |
| | Weight (Net kg) | 5.4 |
| | Weight (Gross kg) | 7.3 |
| Product Dimension with Stand (WxDxH) | Product Dimension with Stand (WxDxH) (mm) | 610.34 x 237 x 454.8 |
| | Product Dimension with Stand (WxDxH) (inch) | 24.03 x 9.33 x 17.91 |
| Weight | Weight Without Stand (kg) | 4.31 |
| Outer Carton Dimension (WxDxH) | Outer Carton Dimension (WxDxH) (mm) | 699 x 173 x 499 |
| | Outer Carton Dimension (WxDxH) (inch) | 27.52 x 6.81 x 19.65 |
| Warranty | Warranty | 24M |
| Accessories | DisplayPort Cable | 0 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | Mouse Bungee Unit | 0 |
| | VESA Screw | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 0 |
| | Warranty Card | 0 |
| Quick Guide | 1 | |
| Barcode Info | EAN | 4719072913526 |
| Display | Screen Size | 27" (69 cm) |
| | Active Display Area (mm) | 597.888(H) x 336.312(V) |
| | Curvature | Curve 1500R |
| | Panel Type | VA |
| | Resolution | 1920x1080 (FHD) |
| | Pixel pitch (mm) | 0.3114(H)x0.3114(V) |
| | HDR (High dynamic range) | N/A |
| | Refresh Rate | 75Hz |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 5ms |
| | View Angles | 178°(H)/178°(V) |
| | sRGB (CIE1976 area percentage/overlap) | 97.7%/94.1% |
| | sRGB (CIE1931 area percentage/overlap) | 102.3%/96.6% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 83.7%/82.6% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 75.8%/74.8% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 77.8%/77.7% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 75.4%/75.3% |
| | Rec.709 (CIE1976 area percentage/overlap) | 97.7%/94.1% |
| | Rec.709 (CIE1931 area percentage/overlap) | 102.3%/96.6% |
| | Rec.2020 (CIE1976 area percentage/overlap) | 56.7%/56.7% |
| Rec.2020 (CIE1931 area percentage/overlap) | 54.1%/54.1% | |
| Display Colors | 16.7M | |
| Color bit | 8 bits | |
| Model | Part No | 9S6-3PA8CT-001 |
| | MKT Name | PRO MP271C |
| | MKT Spec | PRO MP271C |
| | Color | ID1/Black-Black |
| | Model | 3PA8 |
| | Entity MKT Name | PRO MP271C |