

Business & Productivity Monitor



Picture and logos

SELLING POINTS

- Wbudowana kamera internetowa FHD z cyfrowym mikrofonem i zaślepką.
- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie oczu.
- Technologia MSI EyesErgo z systemem Anti-flicker zapobiega nadwyreżeniu oraz zmęczeniu oczu i pomaga chronić Twój wzrok.
- 120-hercowa częstotliwość odświeżania oferuje lepsze wrażenia wizualne i sprawia, że obraz pozbawiony jest efektu migotania.
- Funkcja MSI Eye-Q Check pomaga w samodzielnej kontroli wzroku i przypomina o konieczności odpoczynku podczas długotrwałego korzystania z monitora.
- Podstawa monitora charakteryzuje się szeregiem ergonomicznych funkcji, w tym regulacją nachylenia i wysokości, rotacją wokół osi oraz możliwością obrotu ekranu o 90° (pivot).
- Regulowana podstawa oferująca możliwość zamontowania z tyłu monitora komputera mini-PC zapewnia dużo bardziej ergonomiczną i przejrzystą konfigurację sprzętu, zwiększając tym samym komfort użytkownika i porządek na biurku.
- Zgodność ze standardem montażowym VESA i slot na akcesoria.
- Dwa wbudowane głośniki.



1. 5-way Navigator
2. AC-in
3. 1x Headphone-out
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@120Hz)
6. 1x D-Sub (VGA)
7. 2x USB 2.0 Type-A
8. 1x USB 2.0 Type-B
9. Kensington Lock



MONITORY Z SERII BUSINESS
PRODUCTIVITY

PRO MP272PMG

PRO MP272PMG

SPECIFICATION

Model	SKU Number	9S6-3PD99T-001
	Entity MKT Name	PRO MP272PMG
	Part No	9S6-3PD99T-001
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888 (H) x 336.312 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	47.11~144.23 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	101%/82%
	NTSC (CIE1931 area percentage/overlap)	81%/74%
	sRGB (CIE1976 area percentage/overlap)	116%/99%
	sRGB (CIE1931 area percentage/overlap)	114%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	100%/86%
	Adobe RGB (CIE1931 area percentage/overlap)	84%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	93%/90%
	DCI-P3 (CIE1931 area percentage/overlap)	84%/83%
	Rec.709 (CIE1976 area percentage/overlap)	116%/99%
	Rec.709 (CIE1931 area percentage/overlap)	114%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	60%/60%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Lock type	Kensington Lock
	Speaker	2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	20 (SDR) 25 (HDR)
	Annual Energy Consumption (KWh)	65
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) F (HDR)
	Power Cord Type	C13



MONITORY Z SERII BUSINESS
PRODUCTIVITY

PRO MP272PMG

PRO MP272PMG

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	612 x 227 x 429
	Product Dimension without Stand (WxDxH) (mm)	612 x 46 x 357
	Stand Dimension (WxDxH) (mm)	260 x 227 x 412
	Weight (Net kg)	6.2
	Weight Without Stand (kg)	3.5
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	83.9 x 13.1 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	85.4 x 14.6 x 47.1
	Weight (Gross kg)	8.5
Barcode Info	EAN	4711377260442