

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Ciesz się wysokiej jakości rozrywką dzięki 144-hercowej częstotliwości odświeżania i technologii AMD FreeSync™.
- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie oczu.
- Technologia MSI EyesErgo z systemem Anti-flicker zapobiega nadwyrężeniu oraz zmęczeniu oczu i pomaga chronić Twój wzrok.
- Funkcja MSI Eye-Q Check pomaga w samodzielnej kontroli wzroku i przypomina o konieczności odpoczynku podczas długotrwałego korzystania z monitora.
- Ciesz się wszechstronną współpracą z różnymi urządzeniami, korzystając z wielu wejściowych źródeł sygnału wideo, takich jak porty HDMI™, DisplayPort i D-Sub (VGA).
- Ciesz się porządkiem na biurku dzięki wygodnemu, zdejmowanemu i umieszczonemu na tylnej stronie stopki monitora uchwytowi do prowadzenia kabli.
- Zgodność ze standardem montażowym VESA i slot na akcesoria.



1. 5-Way Navi Key
2. 1x DisplayPort 1.2a
3. 1x HDMI™ 2.0 (FHD@144Hz)
4. 1x D-Sub (VGA)
5. 1x Headphone-out
6. DC-in
7. Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3PB4CH-250	
	Entity MKT Name	PRO MP273 E14A	
	Part No	9S6-3PB4CH-250	
	Color	ID1/Black-Black	
Display	Screen Size	27" (68.58 cm)	
	Active Display Area (mm)	597.888(H) x 336.312(V)	
	Curvature	Flat	
	Panel Type	IPS	
	Resolution	1920x1080 (FHD)	
	Pixel pitch (mm)	0.3114(H)x0.3114(V)	
	Aspect Ratio	16:9	
	Dynamic Refresh Rate technology	FreeSync	
	Dynamic Refresh Rate Activated Range	48~144Hz	
	HDR (High dynamic range)	HDR Ready	
	SDR Brightness (nits)	250	
	Contrast Ratio	1500:1	
	DCR (Dynamic Contrast Ratio)	100000000:1	
	Signal Frequency	53.8~143.2 KHz(H) / 48~144 Hz(V)	
	Refresh Rate	144HZ	
	Response Time (MPRT)	1ms(MPRT)	
	Response Time (GTG)	4ms	
	View Angles	178°(H)/178°(V)	
	NTSC (CIE1976 area percentage/overlap)	89%/74%	
	NTSC (CIE1931 area percentage/overlap)	70%/66%	
	sRGB (CIE1976 area percentage/overlap)	102%/90%	
	sRGB (CIE1931 area percentage/overlap)	99%/88%	
	Adobe RGB (CIE1976 area percentage/overlap)	88%/78%	
	Adobe RGB (CIE1931 area percentage/overlap)	73%/70%	
	DCI-P3 (CIE1976 area percentage/overlap)	82%/78%	
	DCI-P3 (CIE1931 area percentage/overlap)	73%/72%	
	Rec.709 (CIE1976 area percentage/overlap)	102%/90%	
	Rec.709 (CIE1931 area percentage/overlap)	99%/88%	
	Rec.2020 (CIE1976 area percentage/overlap)	59%/59%	
	Rec.2020 (CIE1931 area percentage/overlap)	52%/52%	
Surface Treatment	Anti-glare		
Display Colors	16.7M		
Color bit	8 bits (6 bits + FRC)		
I/O Ports	D-Sub	1	
	Headphone-out	1	
	Card reader	N/A	
	Lock type	Kensington Lock	
	Speaker	3Wx 2	
	HDMI	1	
	HDMI version	2.0	
	HDMI HDCP version	1.4	
	DisplayPort	1	
	DisplayPort version	1.2a	
	DisplayPort HDCP version	1.3	
	Warranty	Warranty	36M
	Power	Power Type	External Adaptor 12V 3A
Power Input		100~240V, 50/60Hz	
On-mode Power Consumption (KWh/1000h)		17	
Annual Energy Consumption (KWh)		17	
Standby-mode Power Consumption (W)		0.5	
Off-mode Power Consumption (W)		0.3	
Energy Efficiency Rating		D	
Power Cord Type	C13 (Optional)		



MONITORY Z SERII BUSINESS
PRODUCTIVITY

PRO MP273 E14A

PRO MP273 E14A

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	optional
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.49 x 201.01 x 470.61
	Product Dimension without Stand (WxDxH) (mm)	613.49 x 59.56 x 364.46
	Stand Dimension (WxDxH) (mm)	240.54 x 201.01 x 178.92
	Weight (Net kg)	4.1
	Weight Without Stand (kg)	3.65
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 45.1
	Outer Carton Dimension (WxDxH) (cm)	70.3 x 14.1 x 47.5
	Weight (Gross kg)	6.3
Barcode Info	EAN	4711377349284