

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Ciesz się wysokiej jakości rozrywką dzięki 144-hercowej częstotliwości odświeżania.
- Certyfikat TÜV potwierdza skuteczną ochronę wzroku i dbałość o zdrowie oczu użytkownika.
- Technologia MSI EyesErgo z systemem Anti-Flicker ogranicza migotanie obrazu, zapobiega nadwyrężeniu wzroku i zmniejsza zmęczenie oczu podczas długotrwałego użytkowania.
- Funkcja MSI Eye-Q Check pozwala na samodzielną kontrolę wzroku oraz przypomina o konieczności regularnych przerw w pracy przy monitorze.
- Szerokie możliwości podłączeń – obsługa wielu źródeł sygnału wideo, w tym portów HDMI™ oraz DisplayPort, zapewnia wygodną współpracę z różnymi urządzeniami.
- Ciesz się schludnym otoczeniem dzięki wygodnej konstrukcji do zarządzania kablami.
- Zgodność ze standardem montażowym VESA i slot na akcesoria.



1. 5-Way Navi Key
2. AC-in
3. 2x HDMI™ 2.0b (WQHD@144Hz)
4. 1x DisplayPort 1.2a
5. 1x Headphone-out
6. Kensington Lock

SPECIFICATION

Model	Entity MKT Name	PRO MP275Q E14
	Part No	9S6-3PF2CM-003
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~144Hz
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	70.56~211.68 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/78%
	NTSC (CIE1931 area percentage/overlap)	78%/70%
	sRGB (CIE1976 area percentage/overlap)	115%/95%
	sRGB (CIE1931 area percentage/overlap)	110%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	95%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	80%/72%
	DCI-P3 (CIE1976 area percentage/overlap)	90%/85%
	DCI-P3 (CIE1931 area percentage/overlap)	80%/78%
	Rec.709 (CIE1976 area percentage/overlap)	115%/95%
	Rec.709 (CIE1931 area percentage/overlap)	110%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	65%/65%
	Rec.2020 (CIE1931 area percentage/overlap)	58%/58%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	



MONITORY Z SERII BUSINESS
PRODUCTIVITY

PRO MP275Q E14

PRO MP275Q E14

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.54 x 206.8 x 456.47
	Product Dimension without Stand (WxDxH) (mm)	613.54 x 51.57 x 361.52
	Stand Dimension (WxDxH) (mm)	218.84 x 206.8 x 146.22
	Weight (Net kg)	4.05
	Weight Without Stand (kg)	3.53
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 45
	Outer Carton Dimension (WxDxH) (cm)	70.8 x 14.8 x 48
	Weight (Gross kg)	6.42
Barcode Info	EAN	4711377392785