

Be Your Window To The World



Picture and logos

SELLING POINTS

- Monitor dokujący udostępna większość swoich funkcji, po podłączeniu go za pomocą tylko jednego kabla Type-C.
- Obsługa funkcji zasilania Type-C 98W Power Delivery, wyświetlania obrazu z wielu źródeł oraz przełącznika KVM.
- Połączenie łańcuchowe (Daisy Chain) z wielostrumieniową transmisją danych zgodną ze standardem DisplayPort.
- Wbudowana kamera internetowa FHD z cyfrowym mikrofonem.
- Wbudowana gigabitowa karta RJ45 Ethernet pozwalająca na uzyskanie stabilnego, przewodowego połączenia sieciowego.
- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie Twoich oczu.
- Technologia MSI EyesErgo z systemem Anti-flicker zapobiega nadwyrężeniu i zmęczeniu oczu oraz pomaga chronić Twój wzrok.
- 100-hercowa częstotliwość odświeżania oferuje lepsze wrażenia wizualne i sprawia, że obraz pozbawiony jest efektu migotania.
- Funkcja MSI Eye-Q Check pomaga w samodzielnej kontroli wzroku i przypomina o konieczności odpoczynku podczas długotrwałego korzystania z monitora.
- Regulowana podstawa oferująca możliwość zamontowania z tyłu monitora komputera mini-PC zapewnia dużo bardziej ergonomiczną i przejrzystą konfigurację sprzętu, zwiększając tym samym komfort użytkownika i porządek na biurku.
- Zgodność ze standardem montażowym VESA i slot na akcesoria.
- Dwa wbudowane głośniki.



1. DC-Jack
2. 2x HDMI™ 2.0b (WQHD@100Hz)
3. 1x DisplayPort 1.2a Input
4. 1x Type-C (DP Alt.) w/ 98W PD
5. 1x DisplayPort 1.2a Output
6. 1x USB 5Gbps Type-B
7. 1x LAN Port
8. 4x USB 5Gbps Type-A
9. Headphone-out
10. 1x Kensington Lock
11. 5-Way Navigator

SPECIFICATION

Model	SKU Number	9S6-3PC8CM-001	
	Entity MKT Name	PRO MP275QPDG	
	Part No	9S6-3PC8CM-001	
	Color	ID1/Black-Black	
Display	Screen Size	27" (68.58 cm)	
	Active Display Area (mm)	596.736(H) x 335.664(V)	
	Curvature	Flat	
	Panel Type	IPS	
	Resolution	2560x1440 (WQHD)	
	Pixel pitch (mm)	0.2331(H)x0.2331(V)	
	Aspect Ratio	16:9	
	Dynamic Refresh Rate technology	Adaptive-Sync	
	Dynamic Refresh Rate Activated Range	48~100Hz	
	HDR (High dynamic range)	HDR Ready	
	SDR Brightness (nits)	250	
	Contrast Ratio	1300:1	
	DCR (Dynamic Contrast Ratio)	100000000:1	
	Signal Frequency	71.04~186.3 KHz(H) / 48~100 Hz(V)	
	Refresh Rate	100HZ	
	Response Time (MPRT)	1ms(MPRT)	
	Response Time (GTG)	4ms	
	View Angles	178°(H)/178°(V)	
	NTSC (CIE1976 area percentage/overlap)	87%/81%	
	NTSC (CIE1931 area percentage/overlap)	74%/72%	
	sRGB (CIE1976 area percentage/overlap)	100%/95%	
	sRGB (CIE1931 area percentage/overlap)	105%/95%	
	Adobe RGB (CIE1976 area percentage/overlap)	85%/84%	
	Adobe RGB (CIE1931 area percentage/overlap)	77%/75%	
	DCI-P3 (CIE1976 area percentage/overlap)	79%/79%	
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%	
	Rec.709 (CIE1976 area percentage/overlap)	100%/95%	
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%	
	Rec.2020 (CIE1976 area percentage/overlap)	58%/58%	
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%	
	Surface Treatment	Anti-glare	
Display Colors	1.07B		
Color bit	10 bits (8 bits + FRC)		
I/O Ports	USB Type C (DisplayPort Alternate)	1	
	Headphone-out	1	
	USB 3.2 Gen 1 Type A	4	
	USB 3.2 Gen 1 Type B	1	
	Lock type	Kensington Lock	
	Speaker	2Wx 2	
	HDMI	2	
	HDMI version	2.0b	
	HDMI HDCP version	2.3	
	DisplayPort	1	
	DisplayPort version	1.2a	
	DisplayPort HDCP version	2.3	
	Warranty	Warranty	36M
Power	Power Type	Internal Power Board	
	Power Input	100~240V, 50/60Hz	
	On-mode Power Consumption (KWh/1000h)	26	
	Annual Energy Consumption (KWh)	38	
	Standby-mode Power Consumption (W)	0.5	
	Off-mode Power Consumption (W)	0.3	
	Energy Efficiency Rating	F	
Power Cord Type	C13		

PRO MP275QPDG

PRO MP275QPDG

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	1
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	614.0 x 233.9 x 578.9
	Product Dimension without Stand (WxDxH) (mm)	614.0 x 53.6 x 377.4
	Stand Dimension (WxDxH) (mm)	300.0 x 233.9 x 422.6
	Weight (Net kg)	7.05
	Weight Without Stand (kg)	4.38
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	83.1 x 13.3 x 46.8
	Outer Carton Dimension (WxDxH) (cm)	85 x 15 x 50
	Weight (Gross kg)	10.24
Barcode Info	EAN	4711377238182