

ОКНО В БОЛЬШОЙ МИР


Серия моноблоков MSI Modern – это не только функциональность, ориентированная на потребности пользователей, но и безупречный дизайн, отражающий мастерство разработчиков и следование модным тенденциям. Такое устройство будет не только полезным инструментом, но и стильным дополнением к вашему образу жизни.



Picture and logos

SELLING POINTS

- Windows 10 Домашняя - MSI рекомендует Windows 11 Pro для бизнеса.
- 23.8" IPS панель с LED подсветкой (1920 x 1080 FHD)
- Процессор Intel® Tiger Lake с памятью DDR4
- Встроенная веб-камера
- MSI технология Anti-Flicker (подавление мерцания экрана) и Less Blue Light (снижение интенсивности синего света)
- Регулируемая подставка обеспечивает наилучшее положение во время работы и обучения дома
- 10-точечный сенсорный экран
- Технология Instant Display позволяет моноблоку переходить в режим монитора без загрузки системы
- Конструкция MSI Storage Rapid Upgrade Design позволяет быстро обновлять или обслуживать 2,5" системы хранения данных
- USB 3.2 Gen 2 Type C с реверсивным дизайном & USB 3.2 Gen 2 Type A обеспечивает наилучшую передачу данных & поддержка Super Charger
- Бесшумная система охлаждения PRO: Термомодуль серверного класса обеспечивает бесшумную и стабильную работу с более длительным сроком службы
- *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see <https://www.microsoft.com/en-us/windows/windows-11-specifications>).
- DataSheet: Общие Характеристики серии Modern AM242TP 11M (pdf)



1. 2x USB3.2 Gen 2 Type C
2. 2x USB3.2 Gen 2 Type A
3. 1x Mic-in/Headphone-out combo
4. 1x Переключаемый 2.5-дюймовый накопитель
5. 5-поз. навигационный модуль
6. 1x DC-in
7. 1x слот замка Кенсингтона
8. 1x HDMI™ in
9. 1x HDMI™ out
10. 2x USB 2.0 Type A
11. 1x RJ45 LAN
12. 1x веб-камера со шторкой

SPECIFICATION

Operating Systems	Operating Systems	Windows 11 Home
	OS	SINGLE-LANGUAGE(WIN 11 HOME SL OLC OA3 EM)
Model	Part No	9S6-AE0122-1059
	MKT Name	Modern AM242TP 11M
	MKT Spec	Modern AM242TP 11M-1059RU
	Color	ID1/White-White-White
Input Device	WebCam	internal webcam
I/O Ports	Lock type	Kensington
Processor	CPU Number	Intel Core i5-1135G7
	CPU Clock	2.4GHz
	CPU Cores	4
	TDP	28W
	Cache	8 MB Intel® Smart Cache
	Threads	8
Chipset	Chipsets	N/A
Memory	Memory Size	8GB(8GB*1)
	Memory Type	DDR4 SDRAM
	Memory Speed	1600(3200)MHZ
	Module Type	SO-DIMM
	слотов памяти (Всего/Свободных)	2/1
	Max Capacity	Max 64GB
Storage	SSD Size	512GB
	HDD1 Size	N/A
	SSD Config	512GB*1
	SSD Interface	PCIe GEN3x4
	SSD Form Factor	M.2-2280 M-KEY
	M.2 slots (Total/Free)	1/0
	HDD1 RPM	N/A
	HDD1 Form Factor	N/A
	HDD1 Interface	N/A
	отсеков для приводов 3.5" (Всего/Свободных)	0/
	отсеков для приводов 2.5" (Всего/Свободных)	1/1
	ODD(Type)	N/A
	ODD Height	N/A
	ODD Type	N/A
Communications	LAN	Realtek RTL8111H
	WLAN	INTEL/AX201.NG.WG.NVW
	WLAN Version	802.11ax 2x2+BT
	BT Version	5.2
Audio	Audio Chipset	Realtek ALC233
	Audio Type	2.1 Channel HD Audio
I/O Ports (Front)	USB 3.2 Gen 2 Type A	2
	USB 3.2 Gen 2 Type C	2
	Mic-in/Headphone-out combo	1
I/O Ports (Rear)	USB 2.0 Type A (R)	2
	RJ45	1
	HDMI™ out	1x (v2.0)
	HDMI™ in	1
Power	AC Adapter Output	120W
	Battery	N/A
	Battery Whrs	N/A

In The Box	Keyboard Interface	USB
	Mouse Interface	USB
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Quick Guide	2
	User Manual	1
	VESA Mount kit	N/A
	Keyboard	SK9626MW
	Mouse	SM9023MW
Design	Adjustment (Tilt)	-4~20
	Adjustment (Swivel)	N/A
	Adjustment (Height)	0~130mm
	Adjustment (Pivot)	N/A
Dimension & Weight	Weight (Net kg)	6.16
	Weight (Gross kg)	8.45
	Product Dimension with Holder (WxDxH) (mm)	N/A
	Product Dimension with Holder (WxDxH) (inch)	N/A
	Inside Carton Dimension with Holder (WxDxH) (mm)	N/A
	Inside Carton Dimension with Holder (WxDxH) (inch)	N/A
	Inside Carton Dimension with Stand (WxDxH) (mm)	N/A
	Inside Carton Dimension with Stand (WxDxH) (inch)	N/A
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	541.4 x 194.68 x 534.92
	Product Dimension with Stand (WxDxH) (inch)	21.31 x 7.66 x 21.06
Warranty	Warranty	12M
Regulatory Compliance	Operating, Storage Temperature	0° C ~ 35° C ; -20° C ~ 60° C
	Operating, Storage Humidity	0% ~ 85%;0% ~ 90%
	Regulatory Compliance	FCC(Class B) CB/CE UL(CUL) BSMI VCCI RCM(C-Tick)
Barcode Info	EAN	4719072903497