

Окно в большой мир



Picture and logos

SELLING POINTS

- Windows 11 Домашняя - MSI рекомендует Windows 11 Pro для бизнеса
- 23.8" дисплей IPS-класса с широкими углами обзора 178°, со светодиодной подсветкой и разрешением Full-HD (1920x1080 пикселей)
- Процессор до Intel® Core™ i7-12700 Alder Lake и память DDR5
- Экран с частотой обновления 100Гц и технологиями защиты зрения MSI Anti-Flicker и Less Blue Light
- Регулируемая подставка с удобным креплением, не требующим использования инструментов
- Видеовыходы HDMI™ и DP для двух внешних дисплеев
- Встроенная FHD-камера с поддержкой аутентификации Windows Hello
- Программное обеспечение Tobii Aware для защиты конфиденциальности
- Приложение MSI Cloud Center позволяет организовать частное облачное хранилище для файлов с мобильных устройств (под управлением Android или iOS)
- Дискретный модуль dTPM для защиты конфиденциальных данных
- Аудиотехнологии DTS для улучшения качества звука
- Надежность в работе 24/7
- DataSheet: Общие Характеристики серии PRO AP242P 12MA (pdf)



1. 1 x DC Jack
2. 1 x HDMI™ out (2.1)
3. 1 x DisplayPort out (1.4)
4. 1 x RJ-45 Ethernet
5. 1 x USB 3.2 Gen 2 Type C / 1 x USB 3.2 Gen 2 Type A
6. 2 x USB 2.0 Type A
7. 1 x Mic-in
8. 1 x Line-out
9. 1 x Kensington Lock
10. 2 x USB 3.2 Gen 1 Type A

SPECIFICATION

| | | |
|----------------------------|---|--------------------------|
| Model | Part No | 9S6-AE0622-677 |
| | MKT Name | PRO AP242P 12MA |
| | MKT Spec | PRO AP242P 12MA-677RU |
| | Color | ID1/White-White-White |
| | Model | AE06 |
| Operating Systems | Operating Systems | N/A |
| Processor | CPU Number | UMA |
| | CPU Clock | 2.1GHz |
| | CPU Cores | 12 |
| | TDP | 65W |
| | Cache | 25 MB Intel® Smart Cache |
| | Threads | 20 |
| | CPU Core Name | ALDER LAKE |
| | CPU Socket | LGA-1700pin |
| | Max Turbo Frequency | up to 4.90 GHz |
| Chipset | Chipsets | H610 |
| Discrete Graphics | GPU1 VRAM Size | N/A |
| | GPU1 VRAM Type | N/A |
| | GPU1 Vendor | N/A |
| Memory | Memory Type | DDR5 SDRAM |
| | Module Type | SO-DIMM |
| | слотов памяти (Всего/Свободных) | 2/0 |
| | Max Capacity | Max 64GB |
| Storage | SSD Interface | PCIe GEN3x4 |
| | SSD Form Factor | M.2-2280 M-KEY |
| | SSD Config | 512GB*1 |
| | SSD Size | N/A |
| | HDD1 Interface | N/A |
| | HDD1 Form Factor | N/A |
| | HDD1 Size | N/A |
| | HDD1 RPM | N/A |
| | ODD(Type) | N/A |
| | ODD Height | N/A |
| | ODD Type | N/A |
| | M.2 slots (Total/Free) | 1/0 |
| | отсеков для приводов 2.5" (Всего/Свободных) | 1/1 |
| | отсеков для приводов 3.5" (Всего/Свободных) | N/A/0 |
| | mSATA slots(Total) | 2 |
| mSATA slots(Free) | 2 | |
| Audio | Audio Chipset | Realtek ALC897 |
| | Audio Type | 2.1 Channel HD Audio |
| Communications | LAN | Intel I219-V |
| | WLAN Version | Wi-Fi 6E+BT |
| | BT Version | 5.3 |
| | WLAN | INTEL/AX211.NG.WG.NV |
| I/O Ports (Front) | USB 2.0 Type A | N/A |
| | USB 3.2 Gen 1 Type A | 2 |
| | USB 3.2 Gen 1 Type C | N/A |
| | USB 3.2 Gen 2 Type A | N/A |
| | USB 3.2 Gen 2 Type C | N/A |
| | USB 3.2 Gen 2x2 Type C | N/A |
| | USB 3.2 Gen 2x2 Type A | N/A |
| Mic-in/Headphone-out combo | N/A | |
| I/O Ports (Rear) | USB 3.2 Gen 2 Type C (R) | 1 |
| | USB 3.2 Gen 2 Type A (R) | 1 |
| | USB 2.0 Type A (R) | 2 |
| | RJ45 | 1 |
| | Card Reader | N/A |
| | HDMI out | 1x (v2.1) |
| DP out | 1x (v1.4) | |

| | | |
|--------------------------------------|--|------------------------------------|
| I/O Ports (Side) | Headphone-out (HiFi / SPDIF) | N/A |
| Power | AC Adapter Output | 120W |
| | Battery | N/A |
| | Battery Whrs | N/A |
| Design | Adjustment (Tilt) | -4°~20°(+/-2°) |
| | Adjustment (Swivel) | N/A |
| | Adjustment (Height) | N/A |
| | Adjustment (Pivot) | N/A |
| Dimension & Weight | Weight (Net kg) | 4.63 |
| | Weight (Gross kg) | 8 |
| | Product Dimension with Holder (WxDxH) (mm) | N/A |
| | Product Dimension with Holder (WxDxH) (inch) | N/A |
| | Inside Carton Dimension with Holder (WxDxH) (mm) | N/A |
| | Inside Carton Dimension with Holder (WxDxH) (inch) | N/A |
| | Inside Carton Dimension with Stand (WxDxH) (mm) | 620 x 223 x 486 |
| | Inside Carton Dimension with Stand (WxDxH) (inch) | 24.41 x 8.78 x 19.13 |
| | Outer Carton Dimension with Holder (WxDxH) (mm) | N/A |
| Product Dimension with Stand (WxDxH) | Product Dimension with Stand (WxDxH) (mm) | 541.9 x 227.9 x 425.5 |
| | Product Dimension with Stand (WxDxH) (inch) | 21.33 x 8.97 x 16.75 |
| Input Device | WebCam | internal webcam |
| Regulatory Compliance | Operating, Storage Temperature | 0° C ~ 35° C ; -20° C ~ 60° C |
| | Operating, Storage Humidity | 0% ~ 85%;0% ~ 90% |
| | Regulatory Compliance | FCC(Class B), CB/CE, UL(CUL), BSMI |
| Warranty | Warranty | 12months |
| In The Box | Keyboard Interface | USB |
| | Mouse Interface | USB |
| | Power Cord | 1 |
| | AC Adaptor | 1 |
| | Warranty Card | N/A |
| | Quick Guide | 1 |
| | User Manual | 1 |
| | VESA Mount kit | N/A |
| | Keyboard | SK9626MW |
| Mouse | SM9023MW | |
| Barcode Info | EAN | 4711377207751 |
| Display | Screen Size | 23.8" (60cm) |
| | Active Display Area (mm) | 527.04(H) x 296.46(V) |
| | Curvature | Flat |
| | Panel Type | IPS |
| | Resolution | 1920x1080 (FHD) |
| | Brightness (nits) | 250 |
| | Refresh Rate | N/A |
| | Response Time (GTG) | 14ms |
| | View Angles | 178°(H)/178°(V) |
| Touch Screen | Non-touch | |
| Display Colors | 16.7M | |