

## Be Your Window To The World



Picture and logos

### SELLING POINTS

- Windows 10 Домашняя - MSI рекомендует Windows 11 Pro для бизнеса. БЕСПЛАТНОЕ обновление до Windows 11\*
- Процессор Intel Jasper Lake
- Вывод изображения в формате 4K/UHD
- Поддержка двух дисплеев одновременно
- Настройте свой режим с помощью MSI Center
- Высокоскоростной периферийный интерфейс USB 3.2 Gen2
- Программный TPM-модуль для защиты конфиденциальных данных
- Совместимость с VESA-кронштейнами
- \* Точное время получения обновления будет зависеть от конкретного устройства. Доступность приложений и функций зависит от региона. Для работы отдельных функций потребуется наличие определенного оборудования (см. <https://www.microsoft.com/ru-ru/windows/windows-11-specifications>).
- DataSheet: Общие Характеристики серии Cubi N JSL (pdf)



1. 2x USB 3.2 Gen2 Type A
2. 1x Mic-in/ Headphone-out
3. 1x DC Jack
4. 1x VGA out
5. 1x LAN
6. 2x USB 3.2 Gen1 Type A
7. 1x HDMI™ (1.4)



Cubi N JSL

CUBI N JSL-040RU

SPECIFICATION

|                   |                                             |                       |
|-------------------|---------------------------------------------|-----------------------|
| Model             | MKT Name                                    | Cubi N JSL            |
|                   | MKT Spec                                    | Cubi N JSL-040RU      |
|                   | Color                                       | ID1/Black-Black-Black |
| Barcode Info      | EAN                                         | 4719072899608         |
| Operating Systems | Operating Systems                           | Windows 11 Pro        |
| Processor         | CPU Number                                  | Intel Pentium N6000   |
|                   | CPU Clock                                   | 1.1GHz                |
|                   | CPU Cores                                   | 4                     |
|                   | TDP                                         | 6W                    |
|                   | Cache                                       | 4 MB L3 Cache         |
|                   | Threads                                     | 4                     |
|                   | CPU Cooler                                  | Air cooling           |
| Discrete Graphics | VGA I/O Port                                | N/A                   |
|                   | VGA MKT Name                                | N/A                   |
| Chipset           | Chipsets                                    | Soc                   |
| Memory            | Memory Size                                 | 4GB(4GB*1)            |
|                   | Memory Type                                 | DDR4 SDRAM            |
|                   | Memory Speed                                | 1600(3200)MHz         |
|                   | Module Type                                 | SO-DIMM               |
|                   | слотов памяти (Всего/Свободных)             | 2/1                   |
|                   | Max Capacity                                | Max 16GB              |
| Audio             | Audio Chipset                               | Realtek ALC233        |
|                   | Audio Type                                  | 5.1 Channel HD Audio  |
| Communications    | LAN                                         | Realtek RTL8111H      |
|                   | WLAN                                        | INTEL/AX201.NGWG.NVW  |
|                   | WLAN Version                                | 802.11ax 2x2+BT       |
|                   | BT Version                                  | 5.2                   |
| Storage           | SSD Size                                    | 128GB                 |
|                   | HDD1 Size                                   | N/A                   |
|                   | SSD Config                                  | 128GB*1               |
|                   | SSD Interface                               | SATA GEN3             |
|                   | SSD Form Factor                             | M.2-2280 B+M KEY      |
|                   | M.2 slots (Total/Free)                      | 1/0                   |
|                   | HDD1 RPM                                    | N/A                   |
|                   | HDD1 Form Factor                            | N/A                   |
|                   | HDD1 Interface                              | N/A                   |
|                   | отсеков для приводов 3.5" (Всего/Свободных) | 0/                    |
|                   | отсеков для приводов 2.5" (Всего/Свободных) | 0/                    |
|                   | ODD(Type)                                   | N/A                   |
|                   | ODD Height                                  | N/A                   |
|                   | ODD Type                                    | N/A                   |
| I/O Ports (Front) | USB 3.2 Gen 2 Type A                        | 2                     |
|                   | Mic-in/Headphone-out combo                  | 1                     |
| In The Box        | Keyboard Interface                          | N/A                   |
|                   | Mouse Interface                             | N/A                   |
|                   | Power Cord                                  | 1                     |
|                   | AC Adaptor                                  | 1                     |
|                   | Warranty Card                               | 1                     |
|                   | Quick Guide                                 | 1                     |
|                   | User Manual                                 | 1                     |
|                   | VESA Mount kit                              | 1                     |
|                   | Keyboard                                    | N/A                   |
|                   | Mouse                                       | N/A                   |
| I/O Ports (Rear)  | USB 3.2 Gen 1 Type A (R)                    | 2                     |
|                   | RJ45                                        | 1                     |
|                   | VGA out                                     | 1                     |
|                   | HDMI™ out                                   | 1x (v2.0)             |
|                   | Audio jack                                  | 1                     |



Cubi N JSL

CUBI N JSL-040RU

|                       |                                                |                                                                  |
|-----------------------|------------------------------------------------|------------------------------------------------------------------|
| Power                 | Power                                          | 65W                                                              |
|                       | Power Certification                            | N/A                                                              |
|                       | Formfactor                                     | N/A                                                              |
|                       | Type                                           | ADAPTOR                                                          |
| Warranty              | Warranty                                       | 12months                                                         |
| VESA                  | VESA size                                      | 100 x 100 mm                                                     |
| Dimension & Weight    | Product Dimension (WxDxH) (mm)                 | 112 x 116 x 44.47(thin botton cover), 55.5(thick botton cover)   |
|                       | Product Dimension (WxDxH) (inch)               | 4.41 x 4.57 x 44.47(thin botton cover), 55.5(thick botton cover) |
|                       | Inside Carton Dimension (WxDxH) (mm)           | 205 x 220 x 94                                                   |
|                       | Inside Carton Dimension (WxDxH) (inch)         | 8.07 x 8.66 x 3.7                                                |
|                       | Outer Carton Dimension Standard (WxDxH) (mm)   | 221 x 506 x 469                                                  |
|                       | Outer Carton Dimension Standard (WxDxH) (inch) | 8.7 x 19.92 x 18.46                                              |
|                       | Weight (Net kg)                                | 0.47                                                             |
|                       | Weight (Gross kg)                              | 1.25                                                             |
|                       | Liter                                          | 0.45                                                             |
| Regulatory Compliance | Operating, Storage Temperature                 | 0° C ~ 35° C ; -20° C ~ 60° C                                    |
|                       | Operating, Storage Humidity                    | 0% ~ 85%;0% ~ 90%                                                |
|                       | Regulatory Compliance                          | FCC(Class B)<br>CB/CE<br>UL(CUL)<br>BSMI<br>VCCI<br>RCM(C-Tick)  |