

Ничего, кроме игр

Успешно проходя строгое фабричное тестирование, мониторы MSI игровой серии могут похвастаться повышенной надежностью и прочностью



Picture and logos

SELLING POINTS

- Быстрая IPS-панель: низкое время отклика (1 мс GtG) и отличная цветопередача
- Повышенная частота обновления экрана: 180Гц
- Время отклика 1мс GTG
- Широкий цветовой охват – Реалистичное отображение каждого оттенка повышает качество картинки в играх.
- Технология Adaptive-sync – повышенное качество отображения динамичных игровых сцен.
- Режим Night Vision: «ночное зрение» для улучшенной ориентации в темных игровых сценах
- Сверхтонкая экранная рамка: ничто не отвлекает взгляд от изображения
- Комфорт для пользователя: подавление мерцания экрана и снижение интенсивности синего света
- Широкие углы обзора: 178°



1. 5-и позиционный навигационный джойстик
2. DC jack
3. выход на наушники
4. 2 x HDMI™ (2.0b)
5. 1 x Display Port (1.4)
6. 1 x Type-C Port (DP alt.)
7. Kensington lock



М О Н И Т О Р Ы
G274QPF E2
G 2 7 4 Q P F E 2

SPECIFICATION

Model	Entity MKT Name	G274QPF E2
	Part No	9S6-3CC29H-460
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	400
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	64.56~266.4 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	1ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	104%/89%
	NTSC (CIE1931 area percentage/overlap)	88%/83%
	sRGB (CIE1976 area percentage/overlap)	119%/99%
	sRGB (CIE1931 area percentage/overlap)	124%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	102%/94%
	Adobe RGB (CIE1931 area percentage/overlap)	92%/87%
	DCI-P3 (CIE1976 area percentage/overlap)	95%/93%
	DCI-P3 (CIE1931 area percentage/overlap)	91%/91%
	Rec.709 (CIE1976 area percentage/overlap)	119%/99%
	Rec.709 (CIE1931 area percentage/overlap)	124%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	69%/69%
	Rec.2020 (CIE1931 area percentage/overlap)	65%/65%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.2
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	12M
Power	Power Type	External Adaptor 19V 3.42A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



МОНИТОРЫ

G274QPF E2

G 2 7 4 Q P F E 2

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	75x75mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 227.9 x 406.6
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 69.8 x 362.5
	Stand Dimension (WxDxH) (mm)	308.6 x 227.8 x 406.6
	Weight (Net kg)	6.3kg
	Weight Without Stand (kg)	3.95kg
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	82.2 x 13.8 x 46.2
	Outer Carton Dimension (WxDxH) (cm)	83.7 x 15.1 x 48.6
	Weight (Gross kg)	8.5kg
Barcode Info	EAN	4711377123334