

PATH TO THE FUTURE

Introducing the MSI MAG 274CXF esports gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 280Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 274CXF, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Панель Rapid VA – обеспечивает время отклика 0,5мс (GtG, мин.), оптимизирует цвета и яркость экрана
- Высокая частота обновления 280Гц
- Быстрое время отклика 0,5мс (GtG, мин.)
- AI Vision - это новая технология позволяет не только выявить детали в темных областях, но и повысить общую яркость и насыщенность цветов
- Технология Less Blue Light: аппаратное уменьшение энергии синего света



1. 5-позиционный навигационный джойстик
2. DC-in
3. Display Port 1.2a
4. 2x HDMI™ 2.0b(FHD@240Гц)
5. Earphone out
6. Замок Кенсингтонский



МОНИТОРЫ

MAG 274CXF

MAG 274CXF

SPECIFICATION

Model	Part No	9S6-3CE31T-012
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~280Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	309.504~589.120 KHz(H) / 48~280 Hz(V)
	Refresh Rate	280Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	107.5%/83.3%
	NTSC (CIE1931 area percentage/overlap)	85.2%/77%
	sRGB (CIE1976 area percentage/overlap)	123.3%/99.1%
	sRGB (CIE1931 area percentage/overlap)	120.3%/99.7%
	Adobe RGB (CIE1976 area percentage/overlap)	105.7%/88.3%
	Adobe RGB (CIE1931 area percentage/overlap)	89.1%/81.5%
	DCI-P3 (CIE1976 area percentage/overlap)	98.2%/92.2%
	DCI-P3 (CIE1931 area percentage/overlap)	88.7%/86.7%
	Rec.709 (CIE1976 area percentage/overlap)	123.3%/99.1%
	Rec.709 (CIE1931 area percentage/overlap)	120.3%/99.7%
	Rec.2020 (CIE1976 area percentage/overlap)	71.5%/71.5%
	Rec.2020 (CIE1931 area percentage/overlap)	63.6%/63.6%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	12M
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C5



МОНИТОРЫ

MAG 274CXF

MAG 274CXF

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	614 x 250 x 438
	Product Dimension without Stand (WxDxH) (mm)	614 x 77 x 364
	Stand Dimension (WxDxH) (mm)	340 x 250 x 140
	Weight (Net kg)	3.4
	Weight Without Stand (kg)	3.0
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	75 x 15 x 48.8
	Outer Carton Dimension (WxDxH) (cm)	76.5 x 16.5 x 51.5
	Weight (Gross kg)	6.1
Barcode Info	EAN	4711377235112