

PATH TO THE FUTURE

Introducing the MSI MAG 274F esports gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 200Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 274F, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Панель Rapid IPS – обеспечивает время отклика 0,5мс (GtG, мин.), оптимизирует цвета и яркость экрана
- Высокая частота обновления 200Гц
- Быстрое время отклика 0,5мс (GtG, мин.)
- AI Vision - это новая технология позволяет не только выявить детали в темных областях, но и повысить общую яркость и насыщенность цветов
- Технология Less Blue Light: аппаратное уменьшение энергии синего света



1. 5-позиционный навигационный джойстик
2. HDMI™ 2.0b (FHD@200Гц)
3. Display Port 1.2a (HBR2)
4. Headphone out
5. DC-in
6. Kensington Lock

SPECIFICATION

| | | |
|-----------|---|-------------------------|
| Model | Part No | 9S6-3CE41H-026 |
| | Color | ID1/Black-Black |
| Display | Screen Size | 27" (68.58 cm) |
| | Active Display Area (mm) | 597.888(H) x 336.312(V) |
| | Curvature | Flat |
| | Panel Type | Rapid IPS |
| | Resolution | 1920x1080 (FHD) |
| | Pixel pitch (mm) | 0.3114(H)x0.3114(V) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | Adaptive-Sync |
| | Dynamic Refresh Rate Activated Range | 48~200Hz |
| | HDR (High dynamic range) | HDR Ready |
| | SDR Brightness (nits) | 300 |
| | Contrast Ratio | 1000:1 |
| | DCR (Dynamic Contrast Ratio) | 10000000:1 |
| | Signal Frequency | TBD |
| | Refresh Rate | 200HZ |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 0.5ms |
| | View Angles | 178°(H)/178°(V) |
| | NTSC (CIE1976 area percentage/overlap) | N/A |
| | NTSC (CIE1931 area percentage/overlap) | N/A |
| | sRGB (CIE1976 area percentage/overlap) | N/A |
| | sRGB (CIE1931 area percentage/overlap) | N/A |
| | Adobe RGB (CIE1976 area percentage/overlap) | N/A |
| | Adobe RGB (CIE1931 area percentage/overlap) | N/A |
| | DCI-P3 (CIE1976 area percentage/overlap) | N/A |
| | DCI-P3 (CIE1931 area percentage/overlap) | N/A |
| | Rec.709 (CIE1976 area percentage/overlap) | N/A |
| | Rec.709 (CIE1931 area percentage/overlap) | N/A |
| | Rec.2020 (CIE1976 area percentage/overlap) | N/A |
| | Rec.2020 (CIE1931 area percentage/overlap) | N/A |
| | Surface Treatment | Anti-glare |
| | Display Colors | 1.07B |
| Color bit | 10 bits (8 bits + FRC) | |
| I/O Ports | Headphone-out | 1 |
| | Lock type | Kensington Lock |
| | HDMI | 1 |
| | HDMI version | 2.0b |
| | HDMI HDCP version | 2.3 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.2a |
| | DisplayPort HDCP version | 2.3 |
| Warranty | Warranty | 12M |
| Power | Power Type | TBD |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | N/A |
| | Annual Energy Consumption (KWh) | N/A |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0..3 |
| | Energy Efficiency Rating | N/A |
| | Power Cord Type | C13 |

| | | |
|------------------------------|--|---------------|
| In The Box | DisplayPort Cable | 0 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 0 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| Mouse Bungee Unit | 0 | |
| Design | Adjustment (Tilt) | -5° ~ 20° |
| | VESA Mounting | 100x100mm |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm) | N/A |
| | Product Dimension without Stand (WxDxH) (mm) | N/A |
| | Stand Dimension (WxDxH) (mm) | N/A |
| | Weight (Net kg) | N/A |
| | Weight Without Stand (kg) | N/A |
| Dimension & Weight (box) | Inside Carton Dimension (WxDxH) (cm) | N/A |
| | Outer Carton Dimension (WxDxH) (cm) | N/A |
| | Weight (Gross kg) | N/A |
| Barcode Info | EAN | 4711377277105 |