

PATH TO THE FUTURE

Представляем игровой монитор MSI MAG 274CXF, созданный для киберспорта. Этот инновационный монитор оснащен 27-дюймовым дисплеем с разрешением Full HD, сверхбыстрой частотой обновления 280 Гц и минимальным временем отклика 0,5 мс (GtG)



Picture and logos

SELLING POINTS

- Панель Rapid VA – обеспечивает время отклика 0,5мс (GtG, мин.), оптимизирует цвета и яркость экрана.
- Высокая частота обновления 240Гц
- Быстрое время отклика 0,5мс (GtG, мин.)
- AI Vision - это новая технология позволяет не только выявить детали в темных областях, но и повысить общую яркость и насыщенность цветов
- Технология Less Blue Light: аппаратное уменьшение энергии синего света



1. 5-и позиционный навигационный джойстик
2. AC-in
3. 2 x HDMI™ 2.0b (WQHD@144Гц)
4. Display Port 1.4a
5. Выход на наушники
6. AC-in
7. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3CE41H-052
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	128.67~175 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	113%/88%
	NTSC (CIE1931 area percentage/overlap)	89%/80%
	sRGB (CIE1976 area percentage/overlap)	130%/99%
	sRGB (CIE1931 area percentage/overlap)	126%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	111%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	93%/85%
	DCI-P3 (CIE1976 area percentage/overlap)	103%/96%
	DCI-P3 (CIE1931 area percentage/overlap)	93%/90%
	Rec.709 (CIE1976 area percentage/overlap)	130%/99%
	Rec.709 (CIE1931 area percentage/overlap)	126%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	75%/75%
	Rec.2020 (CIE1931 area percentage/overlap)	66%/66%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Warranty	Warranty	12M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 249.7 x 438.5
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 62.1 x 362.5
	Stand Dimension (WxDxH) (mm)	340 x 250 x 143
	Weight (Net kg)	4.7
	Weight Without Stand (kg)	4.2
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.3 x 12.7 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	69.8 x 14 x 46.7
	Weight (Gross kg)	6.55
Barcode Info	EAN	4711377281621