

PATH TO THE FUTURE

Представляем игровой монитор MSI MAG 274QF, созданный для киберспорта. Этот инновационный монитор оснащен 27-дюймовым дисплеем с разрешением WQHD, сверхбыстрой частотой обновления 180 Гц и минимальным временем отклика 0,5 мс (GtG)



Picture and logos

SELLING POINTS

- Rapid IPS панель – Обеспечивает время отклика 0.5мс (GtG, мин.), оптимизирует цвета и яркость экрана.
- Высокая частота обновления 180Гц.
- Время отклика 0.5мс (GtG, мин.) – Уберите разрывы изображения и прерывистую частоту кадров.
- AI Vision – Не только показывает, что скрыто в темноте, но и делает картинку ярче и красивее.
- Less Blue Light – Снижение интенсивности синего света.



1. 5-и позиционный навигационный джойстик
2. DisplayPort 1.4a (HBR2)
3. 2x HDMI™ 2.0b (WQHD@144Гц)
4. Выход на наушники
5. AC-in
6. Kensington Lock



МОНИТОРЫ

MAG 274QF

MAG 274QF

SPECIFICATION

Model	Part No	9S6-3CE41H-027
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	90.57~269.81 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	108%/89%
	NTSC (CIE1931 area percentage/overlap)	89%/84%
	SRGB (CIE1976 area percentage/overlap)	124%/100%
	SRGB (CIE1931 area percentage/overlap)	126%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	106%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	94%/86%
	DCI-P3 (CIE1976 area percentage/overlap)	98%/95%
	DCI-P3 (CIE1931 area percentage/overlap)	93%/92%
	Rec.709 (CIE1976 area percentage/overlap)	124%/100%
	Rec.709 (CIE1931 area percentage/overlap)	126%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	72%/71%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
I/O Ports	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
Warranty	DisplayPort version	1.4a (HBR2)
	DisplayPort HDCP version	2.3
Power	Warranty	12M
	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



МОНИТОРЫ

MAG 274QF

MAG 274QF

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 249.7 x 438.5
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 62.1 x 362.5
	Stand Dimension (WxDxH) (mm)	340 x 250 x 143
	Weight (Net kg)	4.7
Dimension & Weight (box)	Weight Without Stand (kg)	4.2
	Inside Carton Dimension (WxDxH) (cm)	68.3 x 12.7 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	69.8 x 14 x 46.7
Barcode Info	Weight (Gross kg)	6.55
	EAN	4711377278904