

PATH TO THE FUTURE

Встречайте MSI MAG 274UPF E2 - Киберспортивный игровой монитор. Этот ультрасовременный монитор оснащен 27-дюймовым дисплеем 4K UHD с молниеносной частотой обновления 160Гц и малым временем отклика 0.5мс GtG.



Picture and logos

SELLING POINTS

- Панель Rapid IPS – обеспечивает время отклика 0.5мс(GtG, мин.)
- Высочайшее разрешение - 4K UHD
- Высокая частота обновления 160Гц
- Быстрое время отклика 0.5мс(GtG, мин.)
- Интерфейс HDMI™ 2.1: поддержка режима 4K/120Гц, идеально для игровых консолей
- Эргономичная подставка: удобная настройка положения экрана монитора
- Сертификация VESA DisplayHDR 400: расширенный динамический диапазон увеличивает контрастность
- Технология AI Vision: Новая технология AI Vision позволяет не только выявлять детали в темных областях, но и повышать общую яркость и насыщать цвета



1. 5-позиционный навигационный модуль
2. DC Jack
3. Headphone Out
4. 2 x HDMI™ (2.1)
5. 1 x DisplayPort (1.4a)
6. USB Type-C (PD15Вт)
7. слот замка Кенсингтона



МОНИТОРЫ

MAG 274UPF E2

MAG 274UPF E2

SPECIFICATION

Model	SKU Number	9S6-3CC29H-295
	Entity Mkt Name	MAG 274UPF E2
	Part No	9S6-3CC29H-295
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.16(H) x 335.34(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.15525(H)x0.15525(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~160Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	400
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	180~352 KHz (H) / 48~160 Hz(V)
	Refresh Rate	160Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	115%/89%
	NTSC (CIE1931 area percentage/overlap)	95%/85%
	SRGB (CIE1976 area percentage/overlap)	133%/99%
	SRGB (CIE1931 area percentage/overlap)	135%/99%
I/O Ports	Adobe RGB (CIE1976 area percentage/overlap)	113%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	101%/89%
	DCI-P3 (CIE1976 area percentage/overlap)	105%/98%
	DCI-P3 (CIE1931 area percentage/overlap)	100%/96%
	Rec.709 (CIE1976 area percentage/overlap)	133%/99%
	Rec.709 (CIE1931 area percentage/overlap)	135%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	76%/76%
	Rec.2020 (CIE1931 area percentage/overlap)	72%/72%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Power	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
	Power Type	External Adaptor 19V 3.42A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



МОНИТОРЫ

MAG 274UPF E2

MAG 274UPF E2

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
	Adjustment (Tilt)	-5° ~ 20°
Design	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	75x75mm
	Product Dimension with Stand (WxDxH) (mm)	613.5 x 227.8 x 406.6
Dimension & Weight (product)	Product Dimension without Stand (WxDxH) (mm)	613.5 x 69.8 x 362.5
	Stand Dimension (WxDxH) (mm)	308.6 x 227.8 x 406.6
	Weight (Net kg)	6.4
	Weight Without Stand (kg)	3.95
	Inside Carton Dimension (WxDxH) (cm)	84.7 x 14.5 x 49.1
Dimension & Weight (box)	Outer Carton Dimension (WxDxH) (cm)	86.2 x 15.8 x 51.5
	Weight (Gross kg)	8.8
	Barcode Info	EAN
		4711377151610