

PATH TO THE FUTURE

Серия мониторов MSI Optix G отличается повышенной надежностью и прочностью, удобством установки и дружелюбным пользовательским интерфейсом.



Picture and logos

SELLING POINTS

- IPS панель с великолепным качеством изображения: точная цветопередача и высокая яркость
- Формат Full-HD: высокое разрешение обеспечивает четкое и детализированное изображение
- Повышенная частота обновления экрана: 144 Гц
- Низкое время отклика ЖК-матрицы: 1 мс
- Широкий цветовой охват: реалистичное отображение каждого оттенка
- Технология адаптивной синхронизации AMD FreeSync®: повышенное качество отображения динамичных игровых сцен
- Режим Night Vision: «ночное зрение» для улучшенной ориентации в темных игровых сценах
- Безрамочный корпус: идеально для мультимониторных конфигураций
- Комфорт для пользователя Anti-Flicker и Less Blue Light – подавление мерцания экрана и снижение интенсивности синего света
- Широкие углы обзора – 178°



1. 5-way joystick navigator
2. 1x DC jack
3. 2x HDMI™ (1.4b)
4. 1x Display Port (1.2a)
5. 1x Earphone out
6. 1x Kensington lock



М О Н И Т О Р Ы

Optix G271

OPTIX G271

SPECIFICATION

Model	Part No	9S6-3CB51T-018
	MKT Name	Optix G271
	MKT Spec	Optix G271
	SKU Number	0
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~180 KHz(H) / 47~145 Hz(V)
	Activated Range	48Hz-144Hz
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	Response Time (Tr + Tf)	7.5ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	104.9%/83.7%
	NTSC (CIE1931 area percentage/overlap)	84.2%/77.1%
	sRGB (CIE1976 area percentage/overlap)	120.3%/99.4%
	sRGB (CIE1931 area percentage/overlap)	118.9%/99.9%
	Adobe RGB (CIE1976 area percentage/overlap)	103.1%/89.3%
	Adobe RGB (CIE1931 area percentage/overlap)	88.1%/82.3%
	DCI-P3 (CIE1976 area percentage/overlap)	95.8%/92.4%
	DCI-P3 (CIE1931 area percentage/overlap)	87.7%/86.7%
	Rec.709 (CIE1976 area percentage/overlap)	120.3%/99.4%
	Rec.709 (CIE1931 area percentage/overlap)	118.9%/99.9%
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	HDMI™	2
	HDMI™ version	1.4b
	DisplayPort	1
	DisplayPort version	1.2a
	Headphone-out	1
	Lock type	Kensington Lock
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	F
	Adapter's KC safety Number	N/A
	Power Cord Type	C5



М О Н И Т О Р Ы

Optix G271

OPTIX G271

In The Box	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	765 x 183 x 473
	Inside Carton Dimension (WxDxH) (inch)	30.12 x 7.2 x 18.62
	Weight (Net kg)	4.1
	Weight (Gross kg)	6.4
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	612.5 x 219.6 x 454.3
	Product Dimension with Stand (WxDxH) (inch)	24.11 x 8.65 x 17.89
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	461.1 x 219.6 x 267.5
	Stand Dimension (WxDxH) (inch)	18.15 x 8.65 x 10.53
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	612.5 x 63.5 x 368.8
	Product Dimension without Stand (WxDxH) (inch)	24.11 x 2.5 x 14.52
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	780 x 198 x 498
	Outer Carton Dimension (WxDxH) (inch)	30.71 x 7.8 x 19.61
Warranty	Warranty	12M
Barcode Info	EAN	4719072704599
	UPC	824142208229
	UCC14	10824142208226