

PATH TO THE FUTURE

Inspired by the rigorous quality testing in the production of MSI MAG series, MSI MAG series' design is full of symbols of sturdiness and durability. Additionally, to provide quality user experience, MAG series has really simple installation process and a friendly user interface, and will be the best choice for entry level gamers to step into the game world.



Picture and logos

SELLING POINTS

- Изогнутый экран с кривизной 1000R: максимальное погружение в игру
- WQHD: высокое разрешение обеспечивает четкое и детализированное изображение
- Отличные скоростные характеристики: высокая частота обновления экрана (165 Гц) и низкое время отклика (1 мс)
- Режим Night Vision: «ночное зрение» для улучшенной ориентации в темных игровых сценах
- Технология FreeSync Premium: качественное изображение в динамике
- Эргономичная подставка: удобная настройка положения экрана монитора
- Технология Less Blue Light Pro: аппаратное уменьшение энергии синего света (с длиной волны от 415 до 455 нм)
- Функция HDMI™ CEC: поддержка пультов дистанционного управления
- Консольный режим: разрешение FHD/WQHD при частоте кадров 120 Гц, разрешение 2K для консоли PS5
- Безрамочный корпус: идеально для мультимониторных конфигураций



1. 1x Power Jack
2. 1x HDMI™ (2.0b)
3. 1x HDMI™ (2.0b)
4. 1x DisplayPort (1.2a)
5. 1x Earphone out



МОНИТОРЫ

Optix G271CQP

OPTIX G271CQP

SPECIFICATION

Model	Part No	9S6-3CC32H-059
	MKT Name	Optix G271CQP
	MKT Spec	Optix G271CQP
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H)x335.664(V)
	Curvature	Curve 1000R
	Panel Type	VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~165Hz
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~160 KHz(H) / 60~144 Hz(V)
	Refresh Rate	165HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	Response Time (Tr + Tf)	10ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	97%/85%
	NTSC (CIE1931 area percentage/overlap)	85%/83%
	sRGB (CIE1976 area percentage/overlap)	110%/90%
	sRGB (CIE1931 area percentage/overlap)	120%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	95%/88%
	Adobe RGB (CIE1931 area percentage/overlap)	90%/85%
	DCI-P3 (CIE1976 area percentage/overlap)	90%/85%
	DCI-P3 (CIE1931 area percentage/overlap)	90%/90%
	Rec.709 (CIE1976 area percentage/overlap)	110%/90%
	Rec.709 (CIE1931 area percentage/overlap)	120%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	64%/64%
	Rec.2020 (CIE1931 area percentage/overlap)	64%/64%
	Display Colors	16.7M
	Color bit	8 bits
I/O Ports	HDMI™	2
	HDMI™ version	2.0b
	HDMI™ HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
	Headphone-out	1
	Lock type	Kensington Lock
I/O Ports (Rear)	Card Reader	N/A
Power	Annual Energy Consumption (KWh)	32
	Power Type	External Adaptor 19V 2.58A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	G
	Adapter's KC safety Number	N/A
	Power Cord Type	C13
	QC Output Power	N/A
	PD Output Power	N/A



МОНИТОРЫ

Optix G271CQP

OPTIX G271CQP

In The Box	3.5mm Mic Cable	N/A
	Switch Case	N/A
	Portable Screen Protection Case	N/A
	Monitor Hood	N/A
	Speaker (Accessories)	N/A
	DisplayPort Cable	1
	HDMI™ Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	4
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 90 mm
	Adjustment (Pivot)	-5° ~ 5°
	VESA Mounting	75x75mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	780 x 177 x 471
	Inside Carton Dimension (WxDxH) (inch)	30.71 x 6.97 x 18.54
	Weight (Net kg)	5.65
	Weight (Gross kg)	8.3
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	606.4 x 528.4 x 289.4
	Product Dimension with Stand (WxDxH) (inch)	23.87 x 20.8 x 11.39
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	541.4 x 389.1 x 289.4
	Stand Dimension (WxDxH) (inch)	21.31 x 15.32 x 11.39
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	606.4 x 363.0 x 115.1
	Product Dimension without Stand (WxDxH) (inch)	23.87 x 14.29 x 4.53
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	790 x 187 x 493
	Outer Carton Dimension (WxDxH) (inch)	31.1 x 7.36 x 19.41
Weight	Weight Without Stand (kg)	4.0
Warranty	Warranty	12M
Barcode Info	EAN	4719072864323
	UPC	824142263235
	UCC14	10824142263232