МОНИТОРЫ

Optix MAG271CP

OPTIX MAG271CP

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Изогнутый экран с кривизной 1800R: максимальное погружение в игру
- Формат FHD: высокое разрешение обеспечивает четкое и детализированное изображение
- Повышенная частота обновления экрана: 144 Гц
- Низкое время отклика матрицы: 1 мс/li>
- Приложение Gaming OSD: оптимизирует настройки монитора под конкретные игры
- True colors – Широкий цветовой охват: 90% DCI-P3 и 115% sRGB
- Адаптивная синхронизация AMD FreeSync: устранение эффекта "разрыва кадра"
- Anti-Flicker и Less Blue Light – подавление мерцания экрана и снижение интенсивности синего света
- Безрамочный корпус: идеально для мультимониторных конфигураций
- Широкие углы обзора: 178°

1. 1x HDMI™
2. 1x HDMI™
3. 1x Display Port
4. 1x Headset
5. 2x USB 2.0 Type A
6. 1x USB 2.0 Type B
7. 1x Kensington Lock
8. Headset Hanger

“2024-03-27 Changes to the product specifications and errors excepted. The product presentation may differ from the product. Microsoft, Windows, the Windows logo, and DirectX are trademarks or registered trademarks of Microsoft Corporation in the United States and / or other countries. Intel, the Intel logo, Intel Inside, the Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other trademarks and trade names refer to the respective owners or their products.”

Optix MAG271CP

OPTIX MAG271CP

SPECIFICATION

Model	Part No	9S6-3FA64T-057
	MKT Name	Optix MAG271CP
	MKT Spec	Optix MAG271CP
	SKU Number	0
	Color	ID1/Black-Black
	Local Dimming	N/A
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Curve 1800R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch	0.3114(H)X0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	SDR Brightness (nits)	300
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	55.3~162 KHz(H) /48~144 Hz(V)
	Activated Range	HDMI 48~144Hz,DP 48~144Hz
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	Response Time (Tr + Tf)	19.875ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	103.77%/91.6%
	NTSC (CIE1931 area percentage/overlap)	92.4%/87.0%
	sRGB (CIE1976 area percentage/overlap)	119.02%/95.3%
	sRGB (CIE1931 area percentage/overlap)	130.45%/98.7%
	Adobe RGB (CIE1976 area percentage/overlap)	101.99%/91.9%
	Adobe RGB (CIE1931 area percentage/overlap)	96.69%/89.9%
	DCI-P3 (CIE1976 area percentage/overlap)	94.79%/91.0%
	DCI-P3 (CIE1931 area percentage/overlap)	96.17%/92.5%
	Rec.709 (CIE1976 area percentage/overlap)	119.02%/95.3%
	Rec.709 (CIE1931 area percentage/overlap)	130.45%/98.7%
	Display Colors	16.7M
	Color bit	8 bits
I/O Ports	HDMI™	2
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
	Headphone-out	1
	Lock type	Kensington Lock
	USB 2.0 Type B	1
I/O Ports (Front)	USB 2.0 Type A	2
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	F
	Adapter's KC safety Number	N/A
	Power Cord Type	N/A
	QC Output	N/A
	QC Output Power	N/A
	PD Output	N/A
	PD Output Power	N/A

“2024-03-27 Changes to the product specifications and errors excepted. The product presentation may differ from the product. Microsoft, Windows, the Windows logo, and DirectX are trademarks or registered trademarks of Microsoft Corporation in the United States and / or other countries. Intel, the Intel logo, Intel Inside, the Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other trademarks and trade names refer to the respective owners or their products.”

Optix MAG271CP

OPTIX MAG271CP

In The Box	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	0
	Thunderbolt Cable	N/A
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Power Cord	1
	AC Adaptor	0
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Height)	0 ~ 130 mm
	VESA Mounting	100x100mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	790 x 227 x 475
	Inside Carton Dimension (WxDxH) (inch)	31.1 x 8.94 x 18.7
	Weight (Net kg)	6.4
	Weight (Gross kg)	9.1
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	612.02 x 266.45 x 560
	Product Dimension with Stand (WxDxH) (inch)	24.1 x 10.49 x 22.05
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	470 x 266.5 x 422
	Stand Dimension (WxDxH) (inch)	18.5 x 10.49 x 16.61
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	612.02 x 83.4 x 370.8
	Product Dimension without Stand (WxDxH) (inch)	24.1 x 3.28 x 14.6
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	N/A
	Outer Carton Dimension (WxDxH) (inch)	N/A
Warranty	Warranty	12M
Barcode Info	EAN	4719072637330
	UPC	824142184004
	UCC14	10824142184001

“2024-03-27 Changes to the product specifications and errors excepted. The product presentation may differ from the product. Microsoft, Windows, the Windows logo, and DirectX are trademarks or registered trademarks of Microsoft Corporation in the United States and / or other countries. Intel, the Intel logo, Intel Inside, the Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other trademarks and trade names refer to the respective owners or their products.”