

PATH TO THE FUTURE

Продукты серии MAG нацелены на пользователей, в особенности на начинающих геймеров, которые предпочитают удобные в обращении и надежные решения. Тщательно протестированные, они просто стабильно делают то, для чего предназначены.



Picture and logos

SELLING POINTS

- Разрешение 4K: высокая детализация (3840 x 2160 пикселей) при частоте обновления экрана 144 Гц
- Высокая частота обновления экрана: 144Гц
- Интерфейс HDMI™ 2.1: поддержка режима «4K / 120 Гц», идеально для игровых консолей
- Rapid IPS-панель: низкое время отклика (1 мс GtG) и отличная цветопередача
- Игровые функции: технологии искусственного интеллекта для геймеров
- Технология Less Blue Light Premium: аппаратное уменьшение энергии синего света (с длиной волны от 415 до 455 нм)
- HDR400: реалистичная цветопередача, подтвержденная сертификацией VESA HDR Display 400
- Режим Night Vision: «ночное зрение» для улучшенной ориентации в темных игровых сценах
- Встроенный переключатель KVM 2.0: использование одного комплекта периферийных устройств для нескольких компьютеров
- Приложение Gaming OSD: оптимизация настроек монитора под конкретные игры



1. 5-way joystick navigator
2. DC jack
3. 2x HDMI™ (2.1)
4. 1x Display Port (1.4a)
5. 1x Type C
6. 1x USB 2.0 Type B
7. 2x USB 2.0 Type A
8. Headphone Out
9. Kensington Lock



М О Н И Т О Р Ы

Optix MAG281URF

OPTIX MAG281URF

SPECIFICATION

Model	Part No	9S6-3CC8GQ-007
	MKT Name	Optix MAG281URF
	MKT Spec	Optix MAG281URF
	Entity MKT Name	Optix MAG281URF
	Color	ID1/Black-Black
Display	Screen Size	27.9" (70.9 cm)
	Active Display Area (mm)	620.93(H)x341.28(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.16(H)x0.16(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	G-SYNC Compatible
	Dynamic Refresh Rate Activated Range	48 ~ 144Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	300
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	250~325.2 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	1ms
	Response Time (Tr + Tf)	N/A
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	108.22%/86.21%
	NTSC (CIE1931 area percentage/overlap)	86.62%/78.82%
	sRGB (CIE1976 area percentage/overlap)	124.14%/100.00%
	sRGB (CIE1931 area percentage/overlap)	122.30%/100.00%
	Adobe RGB (CIE1976 area percentage/overlap)	106.43%/91.52%
	Adobe RGB (CIE1931 area percentage/overlap)	90.66%/83.34%
	DCI-P3 (CIE1976 area percentage/overlap)	98.86%/95.38%
	DCI-P3 (CIE1931 area percentage/overlap)	90.16%/88.75%
	Rec.709 (CIE1976 area percentage/overlap)	124.14%/100.00%
	Rec.709 (CIE1931 area percentage/overlap)	122.30%/100.00%
	Rec.2020 (CIE1976 area percentage/overlap)	72.06%/72.04%
	Rec.2020 (CIE1931 area percentage/overlap)	64.69%/64.68%
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	HDMI™	2
	HDMI™ version	2.1
	HDMI™ HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	USB 2.0 Type B	1
I/O Ports (Front)	USB 2.0 Type A	2
Power	Annual Energy Consumption (KWh)	N/A
	Power Type	External Adaptor 19V 6.32A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	G
	Adapter's KC safety Number	N/A
	Power Cord Type	C5
	PD Output	Type C
	PD Output Power	5V/3A



МОНИТОРЫ

Optix MAG281URF

OPTIX MAG281URF

In The Box	DisplayPort Cable	1
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	4
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	829 x 171 x 490
	Inside Carton Dimension (WxDxH) (inch)	32.64 x 6.73 x 19.29
	Weight (Net kg)	7.7
	Weight (Gross kg)	10.5
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	638.3 x 233.7 x 408.2
	Product Dimension with Stand (WxDxH) (inch)	25.13 x 9.2 x 16.07
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	303.3 x 233.7 x 402.5
	Stand Dimension (WxDxH) (inch)	11.94 x 9.2 x 15.85
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	638.3 x 57.1 x 375.0
	Product Dimension without Stand (WxDxH) (inch)	25.13 x 2.25 x 14.76
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	844 x 186 x 515
	Outer Carton Dimension (WxDxH) (inch)	33.23 x 7.32 x 20.28
Weight	Weight Without Stand (kg)	4.8
Warranty	Warranty	12M
Barcode Info	EAN	4719072861087
	UPC	824142262092
	UCC14	10824142262099