

Тонкий и Элегантный



Picture and logos

SELLING POINTS

- PerfectEdge - 4-сторонняя тонкая рамка позволяет пользователям полностью погрузиться в мультимедийную систему
- Наслаждайтесь высококачественными изображениями с высокой частотой обновления 120 Гц
- Идеальный 27-дюймовый IPS-экран для программирования и веб-дизайна
- Дисплей с сертификатом TÜV обеспечивает защиту и здоровье зрения
- Технология MSI EyesErgo с технологией Anti-Flicker помогает предотвратить напряжение и усталость глаз
- MSI Eye-Q Check помогает контролировать состояние глаз и напоминает о необходимости отдохнуть при длительном использовании монитора
- Возможность использования нескольких источников входного сигнала, таких как порты HDMI™, DisplayPort и D-Sub (VGA)
- Специальная съемная клипса для аккуратной укладки кабелей
- Стандартное крепление VESA и слот для аксессуаров
- Два встроенных динамика



1. 1x AC-in
2. 1x Выход на наушники
3. 1x DisplayPort 1.2a
4. 1x HDMI 1.4b (FHD@120Гц)
5. 1x D-Sub (VGA)
6. 1x Kensington Lock
7. 1x 5-и позиционный джойстик



МОНИТОРЫ БИЗНЕС И
ПРОДУКТИВНОСТЬ

PRO MP271A E2

PRO MP271A E2

SPECIFICATION

| | | |
|-----------|---|------------------------------------|
| Model | Part No | 9S6-3PD0CT-006 |
| | Color | ID1/Black-Black |
| Display | Screen Size | 27" (69 cm) |
| | Active Display Area (mm) | 597.888 (H) x 336.312 (V) |
| | Curvature | Flat |
| | Panel Type | IPS |
| | Resolution | 1920x1080 (FHD) |
| | Pixel pitch (mm) | 0.3114(H)x0.3114(V) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | Adaptive-Sync |
| | Dynamic Refresh Rate Activated Range | 48~120Hz |
| | HDR (High dynamic range) | HDR Ready |
| | SDR Brightness (nits) | 300 |
| | Contrast Ratio | 1500:1 |
| | DCR (Dynamic Contrast Ratio) | 100000000:1 |
| | Signal Frequency | 47.11~144.23 KHz(H) / 48~120 Hz(V) |
| | Refresh Rate | 120Hz |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 4ms |
| | View Angles | 178°(H)/178°(V) |
| | NTSC (CIE1976 area percentage/overlap) | 101%/82% |
| | NTSC (CIE1931 area percentage/overlap) | 81%/74% |
| | sRGB (CIE1976 area percentage/overlap) | 116%/99% |
| | sRGB (CIE1931 area percentage/overlap) | 114%/100% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 100%/86% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 84%/77% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 93%/90% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 84%/83% |
| | Rec.709 (CIE1976 area percentage/overlap) | 116%/99% |
| | Rec.709 (CIE1931 area percentage/overlap) | 114%/100% |
| | Rec.2020 (CIE1976 area percentage/overlap) | 68%/68% |
| | Rec.2020 (CIE1931 area percentage/overlap) | 60%/60% |
| | Surface Treatment | Anti-glare |
| | Display Colors | 16.7M |
| | Color bit | 8 bits (6 bits + FRC) |
| I/O Ports | D-Sub | 1 |
| | Headphone-out | 1 |
| | Lock type | Kensington Lock |
| | Speaker | 2 |
| | HDMI | 1 |
| | HDMI version | 1.4b |
| | HDMI HDCP version | 1.4 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.2a |
| | DisplayPort HDCP version | 1.3 |
| Warranty | Warranty | 12M |
| Power | Power Type | Power Cable |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | 20 |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0.3 |
| | Energy Efficiency Rating | E |
| | Power Cord Type | C13 |



МОНИТОРЫ БИЗНЕС И
ПРОДУКТИВНОСТЬ

PRO MP271A E2

PRO MP271A E2

| | | |
|------------------------------|--|--------------------|
| In The Box | DisplayPort Cable | 0 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 0 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| | Mouse Bungee Unit | 0 |
| Design | Adjustment (Tilt) | -5° ~ 20° |
| | VESA Mounting | 100x100mm |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm) | 612 x 207 x 432 |
| | Product Dimension without Stand (WxDxH) (mm) | 612 x 46 x 357 |
| | Stand Dimension (WxDxH) (mm) | 219 x 207 x 140 |
| | Weight (Net kg) | 3.8 |
| | Weight Without Stand (kg) | 3.3 |
| Dimension & Weight (box) | Inside Carton Dimension (WxDxH) (cm) | 68.8 x 12.8 x 50.5 |
| | Outer Carton Dimension (WxDxH) (cm) | 70.3 x 14.3 x 52.8 |
| | Weight (Gross kg) | 6.2 |
| Barcode Info | EAN | 4711377236973 |