



МОНИТОРЫ БИЗНЕС И  
ПРОДУКТИВНОСТЬ

PRO MP275QPG

PRO MP275QPG

## ОКНО В БОЛЬШОЙ МИР



Picture and logos

## SELLING POINTS

- Идеальный размер экрана 27 дюйма подходит для рабочего места программиста, кодера и дизайнера веб-сайтов.
- Дисплей с сертификатом TÜV обеспечивает защиту и здоровье зрения.
- Технология MSI EyesErgo с технологией Anti-Flicker и Less Blue Light помогает предотвратить напряжение и усталость глаз.
- Частота обновления 100 Гц обеспечивает лучшее качество изображения без мерцания.
- MSI Eye-Q Check помогает контролировать состояние глаз и напоминает о необходимости отдохнуть при длительном использовании монитора.
- Подставка оснащена эргономичными функциями, включая регулировку наклона, поворота, высоты и угла поворота.
- Возможность использования нескольких источников входного сигнала, таких как порты HDMI™, DisplayPort, обеспечивает универсальность при работе с различными устройствами..
- Стандартное крепление VESA.
- Два встроенных динамика.
- Экологичное решение для защиты окружающей среды.



1. 5-и позиционный навигационный джойстик
2. 1x AC-in
3. 1x HDMI™ 2.0b (WQHD@100Гц)
4. 1x DisplayPort
5. 1x HDMI™ 2.0b (WQHD@100Гц)
6. 1x Headphone-out
7. 1x Замок Кенсингтона



МОНИТОРЫ БИЗНЕС И

ПРОДУКТИВНОСТЬ

## PRO MP275QPG

PRO MP275QPG

## SPECIFICATION

Model	Part No	9S6-3PC39M-069
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%/81%
	NTSC (CIE1931 area percentage/overlap)	74%/72%
	SRGB (CIE1976 area percentage/overlap)	100%/95%
	SRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/84%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	79%/79%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%
	Rec.709 (CIE1976 area percentage/overlap)	100%/95%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	58%/58%
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	12M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



МОНИТОРЫ БИЗНЕС И

ПРОДУКТИВНОСТЬ

## PRO MP275QPG

## PRO MP275QPG

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	1
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	614 x 226.9 x 562.6
	Product Dimension without Stand (WxDxH) (mm)	614 x 55.9 x 361.1
	Stand Dimension (WxDxH) (mm)	259.7 x 226.9 x 411.5
	Weight (Net kg)	6.26
	Weight Without Stand (kg)	3.66
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	9.32
Barcode Info	EAN	4711377231916