

## PATH TO THE FUTURE

The MAG 275UPD E14 Gaming Monitor with 27 inch of IPS, Dual Mode for UHD 144Hz and FHD 288Hz for ultra-smooth visuals. Unleash your full potential.



Picture and logos

## SELLING POINTS

- Dual Mode - Easily switch between different resolutions and refresh rates, allowing user to adjust settings based on the game.
- Console Mode - Optimized for seamless compatibility with gaming consoles like PS5 and Xbox Series X|S.
- Aspect Ratio Options - Choose between multiple aspect ratios for a more personalized gaming experience.



1. 5-way Joystick Navigator
2. AC-in
3. 2x HDMI™ 2.1 (UHD@144Hz)
4. DisplayPort 1.4a (HBR3)
5. Headphone-out
6. Kensington Lock

## SPECIFICATION

Model	Part No	9S6-3CE89M-015
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.1554(H)x0.1554(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	UHD : 48~144Hz, FHD : 48~288Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	UHD:106.1~318.2 KHz(H) / 48~144 Hz(V), FHD:106.1~318.2 KHz(H) / 48~288 Hz(V)
	Refresh Rate	UHD:144Hz, FHD:288Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	TBD/TBD
	NTSC (CIE1931 area percentage/overlap)	TBD/TBD
	sRGB (CIE1976 area percentage/overlap)	TBD/TBD
	sRGB (CIE1931 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1976 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1931 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1976 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1931 area percentage/overlap)	TBD/TBD
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.1 (FRL 6G)
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
Power Cord Type	C13	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	81 x 15 x 46.2
	Outer Carton Dimension (WxDxH) (cm)	83 x 17 x 49
	Weight (Gross kg)	TBD
Barcode Info	EAN	4711377318167