PATH TO THE FUTURE

<h2 style =



Selling Points

• Genuine Windows® 7 Home Premium • Intel® Core™ i3-2100 • 21.5" 1920 x 1080 ; Multi Touch Panel • 2x3W 5.1 channel speakers with THX TRUSTUDIO PRO™ • nVIDIA GeForce GT540M Graphics



Picture and logos

System I/O-Ports



- 1. 5-way joystick navigator
- 2. 1x DC Jack
- **3.** 2x HDMI 1.4b
- 4. 1x Display Port 1.2a
- 5. 1x Earphone out
- 6. 1x Kensington lock



MONITOR

Optix G24C4

Specification

		22 64 (62
	Screen Size	23.6" (60cm)
	Active Display Area (mm)	521.39 (H) x 293.2848 (V)
	Curvature	Curve 1500R
Divilor	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	55.3~162 KHz(H) /48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	
	·	1ms(MPRT)
	Response Time (GTG)	4ms
	Response Time (Tr + Tf)	N/A
	View Angles	178°(H)/178°(V)
Display	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	100.7% / 86.1%
	NTSC (CIE1931 area percentage/overlap)	85.6% / 80.0%
	sRGB (CIE1976 area percentage/overlap)	115.5% / 98.4%
	sRGB (CIE1931 area percentage/overlap)	120.9% / 99.6%
	Adobe RGB (CIE1976 area percentage/overlap)	99.0% / 89.5%
	Adobe RGB (CIE1931 area percentage/overlap)	89.6% / 83.3%
	DCI-P3 (CIE1976 area percentage/overlap)	92.0% / 91.6%
	DCI-P3 (CIE1931 area percentage/overlap)	89.1% / 88.9%
	Rec.709 (CIE1976 area percentage/overlap)	115.5% / 98.4%
	Rec.709 (CIE1931 area percentage/overlap)	120.9% / 99.6%
	Display Colors	16.7M
	Color bit	8 bits
	Note_DP	1920 x 1080 (up to 144Hz)
	Note_HDMI	1920 x 1080 (up to 144Hz)
	Note_DVI	N/A
Onboard Graphics	HDMI	2
I/O Ports	HDMI version	1.4b
	HDMI HDCP version	N/A
	DisplayPort	1
	DisplayPort version	1.2
	DisplayPort HDCP version	N/A
	Thunderbolt version	N/A
	Thunderbolt HDCP version	N/A
	Headphone-out	1
	Lock type	Kensington Lock
I/O Ports (Front)	Thunderbolt	N/A
,, 0 1 0/10 (110/10)	Power Supply Type	External Adaptor 20V 2.25A
Power	Power Input	100~240V, 50/60Hz
	Adapter's KC safety Number	N/A
	Power Cord Type	N/A
	QC Output	N/A
	QC Output Power	N/A
	PD Output	N/A
	PD Output Power	N/A



MONITOR

Optix G24C4

	DisplayPort Cable	0
Accessories	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	0
	Thunderbolt Cable	N/A
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Ouick Guide	1
	Adjustment (Tilt)	-5° ~ 20°
Design	VESA Mounting	100x100mm
Design	Frameless Design	Yes
	Outer Carton Dimension (WxDxH) (mm)	606 x 172 x 409
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	23.86 x 6.77 x 16.1
	Product Dimension with Stand (WxDxH) (mm)	536.7 x 225.3 x 429
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (inch)	21.13 x 8.87 x 16.89
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	536.7 x 67.5 x 326.3
	Product Dimension without Stand (WxDxH) (inch)	21.13 x 2.66 x 12.85
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	536.7 x 225.4 x 429
Stand Dimension (WXDXH)	Stand Dimension (WxDxH) (inch)	21.13 x 8.87 x 16.89
Dimension&Weight	Inside Carton Dimensions (WxDxH) (mm)	606 x 172 x 409
	Inside Carton Dimensions (WxDxH) (inch)	23.86 x 6.77 x 16.1
	Weight (Net kg)	3.4
	Weight (Gross kg)	5
Warranty	Warranty	36M
Barcode Info	EAN	4719072658991