

All About Gaming

Inspired by the rigorous quality testing in the production of MSI Optix G series, MSI Optix G series' design is full of symbols of sturdiness and durability. Additionally, to provide quality user experience, Optix G series has really simple installation process and a friendly user interface, and will be the best choice for entry level gamers to step into the game world.



Selling Points

- IPS Panel – Optimize screen colors and brightness to enhance your viewing experience.
- 165Hz Refresh Rate – Respond faster with smoother frames.
- 1ms Response Time – Eliminate screen tearing and choppy frame rates
- NVIDIA G-SYNC Compatible – Prevent screen tearing or stuttering, producing ultra-smooth lag-free gameplay.
- Night Vision – Smart black tuner to brighten your day by bringing out the fine details in dark areas.
- Wide Color Gamut – Game colors and details will look more realistic and refined.
- Frameless Design – Enjoy the ultimate gaming experience with super narrow bezels.
- Anti-Flicker and Less Blue Light – Game even longer and prevent eye strain and fatigue.
- 178° Wide Viewing Angle – Colors and details will stay sharp a ...



Picture and logos

System I/O-Ports



1. 5-way joystick navigator
2. 2x HDMI (1.4b)
3. 1x Display Port (1.2a)
4. Earphone out
5. DC jack
6. Kensington lock



MONITOR
Optix G273
OPTIX G273

Specification

| | | |
|------------------|---|----------------------------------|
| Display | Screen Size | 27" (69 cm) |
| | Active Display Area (mm) | 597.6 (H) x 336.15 (V) |
| | Curvature | Flat |
| | Panel Type | IPS |
| | Resolution | 1920x1080 (FHD) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | G-SYNC Compatible |
| | HDR (High dynamic range) | N/A |
| | SDR Brightness (nits) | 300 |
| | Contrast Ratio | 1000:1 |
| | DCR (Dynamic Contrast Ratio) | 100000000:1 |
| | Signal Frequency | 96.4~186.7 KHz(H) / 48~165 Hz(V) |
| | Refresh Rate | 165HZ |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 4ms |
| | Response Time (Tr + Tf) | 14ms |
| | View Angles | 178°(H)/178°(V) |
| | Surface Treatment | Anti-glare |
| | NTSC (CIE1976 area percentage/overlap) | 116%/85% |
| | NTSC (CIE1931 area percentage/overlap) | 92%/81% |
| | sRGB (CIE1976 area percentage/overlap) | 131%/99% |
| | sRGB (CIE1931 area percentage/overlap) | 131%/99% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 114%/89% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 97%/83% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 106%/94% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 96%/92% |
| | Rec.709 (CIE1976 area percentage/overlap) | 131%/99% |
| | Rec.709 (CIE1931 area percentage/overlap) | 131%/99% |
| | Rec.2020 (CIE1976 area percentage/overlap) | N/A |
| | Rec.2020 (CIE1931 area percentage/overlap) | N/A |
| | Display Colors | 16.7M |
| | Color bit | 8 bits |
| | Note_DP | 1920 x 1080 (Up to 165Hz) |
| | Note_HDMI | 1920 x 1080 (up to 144Hz) |
| | Note_DVI | N/A |
| Onboard Graphics | HDMI | 2 |
| I/O Ports | HDMI version | 1.4b |
| | HDMI HDCP version | 1.4 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.2a |
| | DisplayPort HDCP version | 1.3 |
| | Headphone-out | 1 |
| | Lock type | Kensington Lock |
| | Speaker | N/A |
| Power | Power Supply Type | External Adapter 19V 2.1A |
| | Power Input | 100~240V, 50/60Hz |
| | Adapter's KC safety Number | N/A |
| | Power Cord Type | C5 |



MONITOR
Optix G273
OPTIX G273

| | | |
|---|--|--------------------------|
| Accessories | DisplayPort Cable | 1 |
| | HDMI Cable | 0 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | Mouse Bungee Unit | N/A |
| | VESA Screw | N/A |
| | Power Cord | 1 |
| | AC Adaptor | 1 |
| | Warranty Card | 1 |
| | Quick Guide | 1 |
| Input Device | WebCam | N/A |
| Design | Adjustment (Tilt) | -5° ~ 20° |
| | VESA Mounting | 100x100mm |
| | Frameless Design | Yes |
| Outer Carton Dimension (WxDxH) | Outer Carton Dimension (WxDxH) (mm) | 865 x 145 x 485 |
| | Outer Carton Dimension (WxDxH) (inch) | 34.06 x 5.71 x 19.09 |
| Product Dimension with Stand (WxDxH) | Product Dimension with Stand (WxDxH) (mm) | 614.9 x 228.38 x 444.6 |
| | Product Dimension with Stand (WxDxH) (inch) | 24.21 x 8.99 x 17.5 |
| Product Dimension without Stand (WxDxH) | Product Dimension without Stand (WxDxH) (mm) | 614.9 x 47.4 x 369.3 |
| | Product Dimension without Stand (WxDxH) (inch) | 24.21 x 1.87 x 14.54 |
| Stand Dimension (WxDxH) | Stand Dimension (WxDxH) (mm) | 475.69 x 228.38 x 267.37 |
| | Stand Dimension (WxDxH) (inch) | 18.73 x 8.99 x 10.53 |
| Dimension&Weight | Inside Carton Dimensions (WxDxH) (mm) | 845 x 128 x 465 |
| | Inside Carton Dimensions (WxDxH) (inch) | 33.27 x 5.04 x 18.31 |
| | Weight (Net kg) | 4.45 |
| | Weight (Gross kg) | 6.7 |
| Weight | Weight Without Stand (kg) | N/A |
| Warranty | Warranty | 36M |
| Barcode Info | EAN | 4719072886097 |