

Be Your Window To The World

The streamlined and edgeless shapes are elegant and generous; the composition of every line and the mastery of every circle demonstrates a high degree of perseverance and persistence. It is no longer just a functional product solely focused on meeting users' demands. It is the representation of a craftsman's spirit of excellence and the unrestrained freedom of fashion attitude. Likewise, the Modern Series have functions that fully meet the needs of users and the appearance that can be integrated into various environments. No matter where you are, you must retain your style and persistence in life.



Selling Points

- Elegant and personalized design fits any corners of your house
- TÜV certified display protects your eyesight and keeps your eyes healthy
- Anti-Flicker and Less Blue Light technologies prevent your eyes from strain & fatigue
- Ergonomically work with the most comfortable position while focusing on your courses and works
- 75 Hz refresh rate provides a better viewing experience
- Keep the flexibility for your different devices with multiple input sources, Type-C, HDMI & DP ports
- Standard VESA mountable design
- Always allow you to join an online conference call with built-in speakers



Picture and logos

System I/O-Ports



1. 1x HDMI (1.4)
2. 1x Type C (HDMI 2.0 signal)
3. 1x DisplayPort (1.2)
4. 1x Headphone-out
5. 1x DC Jack

Specification

| | | |
|------------------|---|-----------------------------|
| Display | Screen Size | 27" (69 cm) |
| | Active Display Area (mm) | 596.736(H) X 335.664(V) |
| | Curvature | Flat |
| | Panel Type | IPS |
| | Resolution | 2560x1440 (WQHD) |
| | Aspect Ratio | 16:9 |
| | SDR Brightness (nits) | 250 |
| | Contrast Ratio | 1000:1 |
| | DCR (Dynamic Contrast Ratio) | 100000:1 |
| | Signal Frequency | 30~112 KHz(H) / 48~75 Hz(V) |
| | Refresh Rate | 75Hz |
| | Response Time (GTG) | 5ms |
| | Response Time (Tr + Tf) | 14ms |
| | View Angles | 178°(H)/178°(V) |
| | Surface Treatment | Anti-glare |
| | NTSC (CIE1976 area percentage/overlap) | 95.10%/80.10% |
| | NTSC (CIE1931 area percentage/overlap) | 77.30%/72.00% |
| | sRGB (CIE1976 area percentage/overlap) | 109.02%/97% |
| | sRGB (CIE1931 area percentage/overlap) | 109.13%/96.20% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 93.34%/85.70% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 80.90%/74.80% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 86.92%/83.20% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 80.45%/79.60% |
| | Rec.2020 (CIE1976 area percentage/overlap) | N/A |
| | Rec.2020 (CIE1931 area percentage/overlap) | N/A |
| | Display Colors | 16.7M |
| | Color bit | 8 bits |
| | Note_DP | 2560 x 1440 (Up to 75Hz) |
| | Note_HDMI | 2560 x 1440 (Up to 75Hz) |
| | Note_DVI | N/A |
| Onboard Graphics | HDMI | 1 |
| I/O Ports | HDMI version | 1.4 |
| | HDMI HDCP version | 2.2 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.2 |
| | DisplayPort HDCP version | 2.2 |
| | USB Type C (DisplayPort Alternate) | 1 |
| | Mic-in upstream | N/A |
| | Headphone-out | 1 |
| | Lock type | Kensington Lock |
| | Speaker | N/A |
| | | |
| Power | Power Supply Type | External Adaptor 19V 3.42A |
| | Power Input | 100~240V, 50/60Hz |
| | Power Cord Type | C13 |



BUSINESS PRODUCTIVITY MONITOR

Modern MD271QPW

MODERN MD271QPW

| | | |
|---|--|----------------------|
| Accessories | DisplayPort Cable | 0 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | Mouse Bungee Unit | N/A |
| | VESA Screw | N/A |
| | Power Cord | 1 |
| | AC Adaptor | 1 |
| | Warranty Card | 1 |
| | Quick Guide | 1 |
| Input Device | WebCam | N/A |
| Design | Adjustment (Tilt) | -5° ~ 20° |
| | Adjustment (Swivel) | -30° ~ 30° |
| | Adjustment (Height) | 0 ~ 110 mm |
| | Adjustment (Pivot) | -90° ~ 90° |
| | VESA Mounting | 75x75mm |
| | Frameless Design | Yes |
| Outer Carton Dimension (WxDxH) | Outer Carton Dimension (WxDxH) (mm) | 893 x 167 x 464 |
| | Outer Carton Dimension (WxDxH) (inch) | 35.16 x 6.57 x 18.27 |
| Product Dimension with Stand (WxDxH) | Product Dimension with Stand (WxDxH) (mm) | 613 x 200 x 401 |
| | Product Dimension with Stand (WxDxH) (inch) | 24.13 x 7.87 x 15.79 |
| Product Dimension without Stand (WxDxH) | Product Dimension without Stand (WxDxH) (mm) | 613 x 72 x 362 |
| | Product Dimension without Stand (WxDxH) (inch) | 24.13 x 2.83 x 14.25 |
| Stand Dimension (WxDxH) | Stand Dimension (WxDxH) (mm) | 230 x 200 x 415 |
| | Stand Dimension (WxDxH) (inch) | 9.06 x 7.87 x 16.34 |
| Dimension&Weight | Inside Carton Dimensions (WxDxH) (mm) | 883 x 157 x 442 |
| | Inside Carton Dimensions (WxDxH) (inch) | 34.76 x 6.18 x 17.4 |
| | Weight (Net kg) | 5.8 |
| | Weight (Gross kg) | 8.44 |
| Weight | Weight Without Stand (kg) | N/A |
| Warranty | Warranty | 36M |
| Barcode Info | EAN | 4719072817589 |