

## All About Gaming

Inspired by the rigorous quality testing in the production of the MSI Gaming series, the MSI design is full of symbols of sturdiness and durability. Additionally, to provide a quality user experience, the MSI gaming series has a straightforward installation process and a friendly user interface and will be the best choice for entry-level gamers to step into the game world.



Picture and logos

## SELLING POINTS

- Rapid IPS - 1ms GTG hızlı tepki süresi sağlar, ekran renklerini ve parlaklığını optimize eder.
- 180Hz Tazeleme Oranı - Daha akıcı karelerle daha hızlı yanıt verir.
- 1ms GTG Tepki Süresi - Görüntüdeki yırtılma ve takılmaları ortadan kaldırır.
- Geniş Renk Gamı - Oyunda renkler ve detaylar daha gerçekçi ve berrak görünecek.
- Adaptive-sync - Yırtılmasız, takılmasız, akıcı oyun deneyimi.
- Gece Görüşü - Akıllı siyah ayarı ile karanlık alanlardaki ince ayrıntıları ortaya çıkarır ve gününüzü aydınlatır.
- Çerçevesiz Tasarım - Süper ince çerçevelerle üstün oyun deneyiminin keyfini çıkarın.
- Anti-Flicker ve Less Blue Light - Daha uzun süre oynayın ve göz yorgunluğunu önleyin.
- 178° Geniş İzleme Açısı - 178° geniş izleme açısı ile renkler ve ayrıntılar daha keskin kalır.



1. 5-way joystick navigator
2. DC jack
3. 2 x HDMI™ (2.0b)
4. 1 x Display Port (1.2a)
5. Headphone out
6. Kensington lock

**SPECIFICATION**

Model	Part No	9S6-3BC01M-027
	Color	ID1/Black-Black
Display	Screen Size	24.5" (62.2cm)
	Active Display Area (mm)	543.744(H)x302.616(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48 ~ 180Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.7~198 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	1ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	86%/80%
	NTSC (CIE1931 area percentage/overlap)	73%/72%
	sRGB (CIE1976 area percentage/overlap)	99%/93%
	sRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	84%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/74%
	DCI-P3 (CIE1976 area percentage/overlap)	78%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%
	Rec.709 (CIE1976 area percentage/overlap)	99%/93%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	56%/56%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	557.1 x 220.1 x 418.5
	Product Dimension without Stand (WxDxH) (mm)	557.1 x 66.4 x 326.9
	Stand Dimension (WxDxH) (mm)	318.0 x 220.1 x 142.5
	Weight (Net kg)	3.24
	Weight Without Stand (kg)	2.87
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	63 x 12.5 x 41.1
	Outer Carton Dimension (WxDxH) (cm)	65 x 14.5 x 44.3
	Weight (Gross kg)	5.13
Barcode Info	EAN	4711377142670