

## All About Gaming


Inspired by the rigorous quality testing in the production of the MSI Gaming series, the MSI design is full of symbols of sturdiness and durability. Additionally, to provide a quality user experience, the MSI gaming series has a straightforward installation process and a friendly user interface and will be the best choice for entry-level gamers to step into the game world.



Picture and logos

## SELLING POINTS

- IPS Panel - Optimize screen colors and brightness to enhance your viewing experience.
- 170Hz Refresh Rate - Respond faster with smoother frames.
- 1ms Response Time - Eliminate screen tearing and choppy frame rates.
- Wide Color Gamut - Game colors and details will look more realistic and refined.
- Night Vision - Smart black tuner to brighten your day by bringing out the fine details in dark areas.
- AMD FreeSync™ Technology - Prevent screen tearing or stuttering, producing ultra-smooth lag-free gameplay.
- Frameless design - Enjoy the ultimate gaming experience with super narrow bezels.
- Anti-Flicker and Less Blue Light - Game even longer and prevent eye strain and fatigue.
- 178° Wide Viewing Angle - Colors and details will stay sharp at more angles with a 178° wide viewing angle.



1. 5-way joystick navigator
2. DC jack
3. 2 x HDMI™ (1.4b)
4. 1 x Display Port (1.2a)
5. Headphone out
6. Kensington lock

**SPECIFICATION**

Barcode Info	EAN	4719072956011
	UPC	824142286296
	UCC14	10824142286293
Model	Part No	9S6-3CB51T-060
	MKT Name	G2712
	MKT Spec	G2712
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	SDR Brightness (nits)	250
	Contrast Ratio	1100:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~100 KHz(H) / 48~170 Hz(V)
	Refresh Rate	170Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	88.86% / 79%
	NTSC (CIE1931 area percentage/overlap)	72.13% / 69.41%
	sRGB (CIE1976 area percentage/overlap)	101.91% / 99.32%
	sRGB (CIE1931 area percentage/overlap)	101.83% / 99.41%
	Adobe RGB (CIE1976 area percentage/overlap)	87.33% / 85.67%
	Adobe RGB (CIE1931 area percentage/overlap)	75.47% / 74.73%
	DCI-P3 (CIE1976 area percentage/overlap)	81.16% / 81.1%
	DCI-P3 (CIE1931 area percentage/overlap)	75.07% / 75.07%
	Rec.709 (CIE1976 area percentage/overlap)	101.91% / 99.32%
	Rec.709 (CIE1931 area percentage/overlap)	101.83% / 99.41%
	Rec.2020 (CIE1976 area percentage/overlap)	59.14% / 59.14%
	Rec.2020 (CIE1931 area percentage/overlap)	53.86% / 53.86%
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
	Note_DP	1920 x 1080 (Up to 170Hz)
	Note_HDMI™	1920 x 1080 (up to 144Hz)
	Note_DVI	N/A
I/O Ports	HDMI™	2
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
	Headphone-out	1
Lock type	Kensington Lock	
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	D
	Adapter's KC safety Number	SU10469-15001
	Power Cord Type	C5

In The Box	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	1
	HDMI™ Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
Quick Guide	1	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	698 x 172 x 488
	Outer Carton Dimension (WxDxH) (inch)	27.48 x 6.77 x 19.21
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	612.5 x 228.2 x 454.0
	Product Dimension with Stand (WxDxH) (inch)	24.11 x 8.98 x 17.87
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	612.5 x 45.0 x 368.3
	Product Dimension without Stand (WxDxH) (inch)	24.11 x 1.77 x 14.5
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	475.7 x 228.2 x 267.5
	Stand Dimension (WxDxH) (inch)	18.73 x 8.98 x 10.53
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	683 x 157 x 463
	Inside Carton Dimension (WxDxH) (inch)	26.89 x 6.18 x 18.23
	Weight (Net kg)	4.1
	Weight (Gross kg)	5.8
Weight	Weight Without Stand (kg)	3.3
Warranty	Warranty	36M