

All About Gaming

Inspired by the rigorous quality testing in the production of the MSI Gaming series, the MSI design is full of symbols of sturdiness and durability. Additionally, to provide a quality user experience, the MSI gaming series has a straightforward installation process and a friendly user interface and will be the best choice for entry-level gamers to step into the game world.



Picture and logos

SELLING POINTS

- Rapid IPS - 1ms GTG hızlı tepki süresi ile ekrandaki renkleri ve parlaklığı optimize eder.
- 180Hz Tazeleme hızı - Akıcı çerçeveler ile daha hızlı tepki
- 1ms GTG Tepki süresi - Görüntüde yırtılma ve takılmaları engeller.
- Geniş renk gamı - Oyunda renk ve detaylar daha gerçekçi
- Adaptive-sync - Ultra akıcı, gecikmesiz, takılmasız oyun deneyimi
- Night Vision - Akıllı siyah renk ayarı ile karanlık bölgelerdeki ince detayları ortaya çıkarır.
- Çerçevesiz tasarım - Süper ince ekran çerçeveleri ile nihai oyun deneyimi.
- Anti-Flicker ve Less Blue Light - Daha az göz yorgunluğu yaşayın ve daha uzun süre oynayın.
- 178° Geniş görüntüleme açısı ile ekrana nereden bakarsanız bakın; renk ve detaylar daha keskin.



1. 5-way joystick navigator
2. DC-in
3. 1 x Display Port (1.4)
4. 2 x HDMI™ (2.0b)
5. Headphone out
6. Kensington lock

SPECIFICATION

Model	Part No	9S6-3CD39T-024
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1200:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	64.56~266.4 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	109%/86%
	NTSC (CIE1931 area percentage/overlap)	90%/82%
	sRGB (CIE1976 area percentage/overlap)	125%/99%
	sRGB (CIE1931 area percentage/overlap)	127%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	107%/90%
	Adobe RGB (CIE1931 area percentage/overlap)	94%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	99%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	94%/92%
	Rec.709 (CIE1976 area percentage/overlap)	125%/99%
	Rec.709 (CIE1931 area percentage/overlap)	127%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	72%/71%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C5

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613 x 228 x 409
	Product Dimension without Stand (WxDxH) (mm)	613 x 61 x 369
	Stand Dimension (WxDxH) (mm)	309 x 228 x 391
	Weight (Net kg)	6.3
	Weight Without Stand (kg)	3.8
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	84 x 15 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	85.5 x 16.5 x 50
	Weight (Gross kg)	8.4
Barcode Info	EAN	4711377141765