

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- En yeni 4.Nesil QD-OLED Panel - Çarpıcı görüntü kalitesi ve hızlı tepki süresi.
- Uniform Luminance - HDR eğri özelleştirmesi ile HDR renk eğrisini tercihinize göre özelleştirebilir ve her noktada yumuşak geçişli bir HDR aydınlatma elde edebilirsiniz
- İnanılmaz HDR Görseller- VESA DisplayHDR True Black 400.
- Sektör standartlarına uygun - Delta E≤2.
- Kristal netliğinde Hareket - VESA ClearMR 9000 sertifikası.
- OLED panel yanmasını da kapsayan 3 Yıl Garanti



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UHD@240Hz)
4. DisplayPort 2.1a (UHBR20)
5. USB Type-C (98W PD)
6. USB Type-B
7. 2x USB Type-A
8. Headphone-out
9. Kensington lock

SPECIFICATION

Model	Part No	9S6-3CD79A-082
	Color	ID1/Black-Black
	Local Dimming	TBD
Display	Screen Size	26.5" (67.31 cm)
	Active Display Area (mm)	589.97(H) x 332.93(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.153(H)x0.153(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	G-SYNC Compatible
	Dynamic Refresh Rate Activated Range	48~165Hz
	HDR (High dynamic range)	VESA DisplayHDR True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	DCR (Dynamic Contrast Ratio)	TBD
	Signal Frequency	280.3~386.8 KHz(H) / 48~165 Hz(V)
	Refresh Rate	165HZ
	Response Time (MPRT)	TBD
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	121%/95%
	NTSC (CIE1931 area percentage/overlap)	105%/92%
	sRGB (CIE1976 area percentage/overlap)	138%/100%
	sRGB (CIE1931 area percentage/overlap)	148%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	119%/98%
	Adobe RGB (CIE1931 area percentage/overlap)	109%/95%
	DCI-P3 (CIE1976 area percentage/overlap)	110%/99%
	DCI-P3 (CIE1931 area percentage/overlap)	109%/99%
	Rec.709 (CIE1976 area percentage/overlap)	138%/100%
	Rec.709 (CIE1931 area percentage/overlap)	148%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80%/80%
	Rec.2020 (CIE1931 area percentage/overlap)	78%/78%
	Surface Treatment	Anti-Reflection
	Display Colors	1.07B
Color bit	10 bits	

I/O Ports	Thunderbolt	N/A
	Thunderbolt version	N/A
	Thunderbolt HDCP version	N/A
	USB Type C (DisplayPort Alternate)	1
	DVI	N/A
	D-Sub	N/A
	Line-in	N/A
	Mic-in	N/A
	Mic-in upstream	N/A
	Headphone-out	1
	Audio Combo	N/A
	USB 2.0 Type A	N/A
	USB 2.0 Type B	N/A
	USB 2.0 Type C	N/A
	USB 3.2 Gen 1 Type A	N/A
	USB 3.2 Gen 1 Type B	N/A
	USB 3.2 Gen 1 Type C	N/A
	USB 3.2 Gen 2x2 Type C	N/A
	USB 3.2 Gen 2x2 Type A	N/A
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	N/A
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
DisplayPort HDCP version	2.3	
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	25.4
	Annual Energy Consumption (KWh)	25.4
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	
In The Box	DisplayPort Cable	1
	HDMI Cable	N/A
	DVI Cable	N/A
	USB Type A to Type B Cable	N/A
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	N/A
	Thunderbolt Cable	N/A
	VGA Cable	N/A
	3.5mm audio Cable	N/A
	3.5mm combo audio Cable	N/A
	3.5mm Mic Cable	N/A
	Power Cord	1
	AC Adaptor	N/A
	Quick Guide	1
	Warranty Card	N/A
	Mouse Bungee Unit	N/A
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 110 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm



MONITOR

MAG 272UP QD-OLED E16

MAG 272UP QD-OLED E16

Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	611.1 x 241.9 x 532.8
	Product Dimension without Stand (WxDxH) (mm)	611.1 x 69.3 x 357.2
	Stand Dimension (WxDxH) (mm)	309 x 241.9 x 432.1
	Weight (Net kg)	6.8
	Weight Without Stand (kg)	4.1
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	81 x 18.5 x 50
	Outer Carton Dimension (WxDxH) (cm)	82.8 x 20 x 52.5
	Weight (Gross kg)	11.
Barcode Info	EAN	4711377410762