

All about gaming



Picture and logos

SELLING POINTS

- Curved Gaming display (1500R) - The best gameplay immersion.
- 144Hz Refresh Rate - Real smooth gaming.
- 1ms response time - eliminate screen tearing and choppy frame rates.
- Wide Color Gamut - Game colors and details will look more realistic and refined, pushing game immersion to its limits
- Night Vision - See every detail clearly in the dark, helping you find and attack enemies before they notice.
- AMD Free - Sync premium Technology - Tear free, stutter free, fluid gaming.
- Anti-Flicker and Less Blue Light - game even longer and prevent eye strain and fatigue.
- Frameless design - Ultimate gameplay experience.
- 178° Wide Viewing Angle - Colors and details will stay sharp at more angles with a 178° wide viewing angle.



1. 5-way joystick navigator
2. 1x HDMI™ (1.4)
3. 1x HDMI™ (1.4)
4. 1x Display Port (1.2)
5. 1x Earphone out
6. 1x Kensington Lock

SPECIFICATION

Barcode Info	EAN	4719072767112
	UPC	824142230572
	UCC14	10824142230579
Model	Part No	9S6-3BA04T-033
	MKT Name	Optix G24C6P
	MKT Spec	Optix G24C6P
	SKU Number	0
	Color	ID1/Black-Black
Display	Screen Size	23.6" (60cm)
	Active Display Area (mm)	521.39 (H) x 293.2848 (V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch	0.27156(H)X0.27156 (V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	55.3~162 KHz(H) /48~144 Hz(V)
	Activated Range	48Hz-144Hz
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	100.7% / 86.1%
	NTSC (CIE1931 area percentage/overlap)	85.6% / 80.0%
	sRGB (CIE1976 area percentage/overlap)	115.5% / 98.4%
	sRGB (CIE1931 area percentage/overlap)	120.9% / 99.6%
	Adobe RGB (CIE1976 area percentage/overlap)	99.0% / 89.5%
	Adobe RGB (CIE1931 area percentage/overlap)	89.6% / 83.3%
	DCI-P3 (CIE1976 area percentage/overlap)	92.0% / 91.6%
	DCI-P3 (CIE1931 area percentage/overlap)	89.1% / 88.9%
	Rec.709 (CIE1976 area percentage/overlap)	115.5% / 98.4%
	Rec.709 (CIE1931 area percentage/overlap)	120.9% / 99.6%
	Display Colors	16.7M
	Color bit	8 bits
	Note_DP	1920 x 1080 (up to 144Hz)
Note_HDMI™	1920 x 1080 (up to 144Hz)	
Note_DVI	N/A	
I/O Ports	HDMI™	2
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2
	DisplayPort HDCP version	1.3
	Headphone-out	1
	Lock type	Kensington Lock
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	F
	Adapter's KC safety Number	SU10469-15001
	Power Cord Type	C5

In The Box	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Height)	0 ~ 130 mm
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	720 x 212 x 434
	Outer Carton Dimension (WxDxH) (inch)	28.35 x 8.35 x 17.09
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	536.7 x 231.2 x 538.3
	Product Dimension with Stand (WxDxH) (inch)	21.13 x 9.1 x 21.19
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	536.7 x 79.74 x 326.3
	Product Dimension without Stand (WxDxH) (inch)	21.13 x 3.14 x 12.85
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	382.59 x 230.9 x 408.56
	Stand Dimension (WxDxH) (inch)	15.06 x 9.09 x 16.09
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	705 x 197 x 409
	Inside Carton Dimension (WxDxH) (inch)	27.76 x 7.76 x 16.1
	Weight (Net kg)	4.5
	Weight (Gross kg)	6.8
Warranty	Warranty	36M