

Be Your Window To The World



Picture and logos

SELLING POINTS

- Perfect 21.5" screen size for the programming, coding & website design workspace.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker technology helps prevent eye strain and fatigue.
- 100 Hz refresh rate provides a better viewing experience with flicker-free image.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™ and D-Sub(VGA) ports.
- Enjoy the cleanest environment with a convenient and removable cable management design.
- Standard VESA mountable & Accessory slot design.



1. 1x DC-in
2. 1x HDMI™ (1.4b)
3. 1x D-Sub (VGA)
4. 1x Headphone-out
5. 1x Kensington Lock
6. 1x 5-way navigator

SPECIFICATION

Model	SKU Number	9S6-3PC6CM-002
	Entity MKT Name	PRO MP225
	Part No	9S6-3PC6CM-002
	Color	ID1/Black-Black
Display	Screen Size	21.5" (55 cm)
	Active Display Area (mm)	476.064(H) x 267.786(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.24795(H)x0.24795(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.704~110.1 KHz (H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	93.24%/80.04%
	NTSC (CIE1931 area percentage/overlap)	73.7%/68.98%
	sRGB (CIE1976 area percentage/overlap)	107.39%/96.64%
	sRGB (CIE1931 area percentage/overlap)	104.88%/96.73%
	Adobe RGB (CIE1976 area percentage/overlap)	91.76%/84.82%
	Adobe RGB (CIE1931 area percentage/overlap)	77.23%/73.27%
	DCI-P3 (CIE1976 area percentage/overlap)	85.11%/84.53%
	DCI-P3 (CIE1931 area percentage/overlap)	76.78%/76.64%
	Rec.709 (CIE1976 area percentage/overlap)	107.39%/96.64%
	Rec.709 (CIE1931 area percentage/overlap)	104.88%/96.73%
	Rec.2020 (CIE1976 area percentage/overlap)	61.47%/61.47%
	Rec.2020 (CIE1931 area percentage/overlap)	54.52%/54.52%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
Color bit	8 bits (6 bits + FRC)	
I/O Ports	D-Sub	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
Warranty	Warranty	24M
Power	Power Type	External Adaptor 12V 2A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	15
	Annual Energy Consumption (KWh)	22
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
Energy Efficiency Rating	E	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	489.4 x 182.3 x 384.8
	Product Dimension without Stand (WxDxH) (mm)	489.4 x 51.3 x 291.5
	Stand Dimension (WxDxH) (mm)	200.5 x 182.3 x 143.8
	Weight (Net kg)	2.3
	Weight Without Stand (kg)	2
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	56.7 x 11.8 x 36.5
	Outer Carton Dimension (WxDxH) (cm)	58.7 x 13.8 x 39.8
	Weight (Gross kg)	4.1
Barcode Info	EAN	4711377180146