

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge - the 4-side slim bezel design allows users to fully immerse themselves in a multi-display setup
- Enjoy the high-quality entertainment with a smoother 120Hz high refresh rate.
- Perfect 27-inch IPS panel for the programming, coding & website design.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker technology helps prevent eye strain and fatigue.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™, DisplayPort and D-Sub (VGA) ports.
- Enjoy the cleanest environment with a convenient and removable cable management design.
- Standard VESA mountable & Accessory Slot design.
- Two built-in speakers.



1. 1x AC-in
2. 1x Headphone-out
3. 1x DisplayPort 1.2a
4. 1x HDMI 1.4b (FHD@120Hz)
5. 1x D-Sub (VGA)
6. 1x Kensington Lock
7. 1x 5-way Navigator

SPECIFICATION

Model	SKU Number	0
	Part No	9S6-3PD0CT-001
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888 (H) x 336.312 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	47.11~144.23 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	101%/82%
	NTSC (CIE1931 area percentage/overlap)	81%/74%
	sRGB (CIE1976 area percentage/overlap)	116%/99%
	sRGB (CIE1931 area percentage/overlap)	114%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	100%/86%
	Adobe RGB (CIE1931 area percentage/overlap)	84%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	93%/90%
	DCI-P3 (CIE1931 area percentage/overlap)	84%/83%
	Rec.709 (CIE1976 area percentage/overlap)	116%/99%
	Rec.709 (CIE1931 area percentage/overlap)	114%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	60%/60%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	24M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	20
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	612 x 207 x 432
	Product Dimension without Stand (WxDxH) (mm)	612 x 46 x 357
	Stand Dimension (WxDxH) (mm)	219 x 207 x 140
	Weight (Net kg)	3.8
	Weight Without Stand (kg)	3.3
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 50.5
	Outer Carton Dimension (WxDxH) (cm)	70.3 x 14.3 x 52.8
	Weight (Gross kg)	6.2
Barcode Info	EAN	4711377236973