

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- 27" ekran boyutu sayesinde programlama, kodlama ve web tasarımı için mükemmel bir ekran alanı sunar.
- TÜV sertifikalı anti-flicker ve less blue light görme duyusunun ve göz sağlığının korunmasına yardımcı olur.
- Anti-Flicker teknolojisi gözlerinizin yorulmasını önler.
- Less Blue Light gözlerinize uzun vadede ciddi zararlar verebilecek mavi ışığı etkili bir şekilde azaltır.
- Eğme, döndürme, yükseklik ve pivot ayarlarına sahip ergonomik tasarımı stand.
- Ergonomik yazılım Display Kit, günlük kullanımda en uygun renk ve görüntüleme modunu sunan kullanışlı bir araçtır.
- IPS sınıfı panel nefes kesici bir ekran netliği sunar.
- 100Hz tazeleme oranı daha iyi bir görüntüleme deneyimi sağlar.
- DisplayPort, HDMI™, and D-Sub portları üzerinden farklı cihazları bağlayabilir, daha esnek çalışabilirsiniz. (VGA)
- Standart VESA montaj tasarımı.
- Dahili hoparlörleri sayesinde online konferans görüşmelerine her zaman hazırsınız.



1. 1x DisplayPort (1.2a)
2. 1x HDMI (1.4b)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x DC-in
6. 1x Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3PB49H-232	
	Entity MKT Name	PRO MP273AP	
	Part No	9S6-3PB49H-232	
	Color	ID1/Black-Black	
Display	Screen Size	27" (69 cm)	
	Active Display Area (mm)	597.888(H)x336.312(V)	
	Curvature	Flat	
	Panel Type	IPS	
	Resolution	1920x1080 (FHD)	
	Pixel pitch (mm)	0.3114(H)x0.3114(V)	
	Aspect Ratio	16:9	
	Dynamic Refresh Rate technology	Adaptive-Sync	
	Dynamic Refresh Rate Activated Range	48~100Hz	
	HDR (High dynamic range)	N/A	
	SDR Brightness (nits)	300	
	Contrast Ratio	1000:1	
	DCR (Dynamic Contrast Ratio)	100000000:1	
	Signal Frequency	52.32~109 KHz (H) / 48~100 Hz(V)	
	Refresh Rate	100HZ	
	Response Time (MPRT)	1ms(MPRT)	
	Response Time (GTG)	4ms	
	View Angles	178°(H)/178°(V)	
	NTSC (CIE1976 area percentage/overlap)	93%/83%	
	NTSC (CIE1931 area percentage/overlap)	76%/74%	
	sRGB (CIE1976 area percentage/overlap)	106%/99%	
	sRGB (CIE1931 area percentage/overlap)	108%/99%	
	Adobe RGB (CIE1976 area percentage/overlap)	91%/88%	
	Adobe RGB (CIE1931 area percentage/overlap)	80%/77%	
	DCI-P3 (CIE1976 area percentage/overlap)	85%/84%	
	DCI-P3 (CIE1931 area percentage/overlap)	79%/79%	
	Rec.709 (CIE1976 area percentage/overlap)	106%/99%	
	Rec.709 (CIE1931 area percentage/overlap)	108%/99%	
	Rec.2020 (CIE1976 area percentage/overlap)	61%/61%	
	Rec.2020 (CIE1931 area percentage/overlap)	57%/57%	
	Surface Treatment	Anti-glare	
	Display Colors	16.7M	
Color bit	8 bits (6 bits + FRC)		
I/O Ports	D-Sub	1	
	Line-in	1	
	Card reader	N/A	
	Lock type	Kensington Lock	
	Speaker	2	
	HDMI	1	
	HDMI version	1.4b	
	HDMI HDCP version	1.4	
	DisplayPort	1	
	DisplayPort version	1.2a	
	DisplayPort HDCP version	1.3	
	Warranty	Warranty	24M
	Power	Power Type	External Adaptor 12V 2.5A
Power Input		100~240V, 50/60Hz	
On-mode Power Consumption (KWh/1000h)		21W	
Annual Energy Consumption (KWh)		21W	
Standby-mode Power Consumption (W)		0.5W	
Off-mode Power Consumption (W)		0.3W	
Energy Efficiency Rating		E	
Power Cord Type	C13		

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 110 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	75x75mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.50 x 200.8 x 413.4
	Product Dimension without Stand (WxDxH) (mm)	613.50 x 48.3 x 362.5
	Stand Dimension (WxDxH) (mm)	230.8 x 200.8 x 402.8
	Weight (Net kg)	5.6
	Weight Without Stand (kg)	3.4
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	84.1 x 13.1 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	85.6 x 14.4 x 47.2
	Weight (Gross kg)	7.6
Barcode Info	EAN	4711377034982