

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Enjoy the high-quality entertainment with a smoother 144Hz high refresh rate.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker technology helps prevent eye strain and fatigue.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™ and DP ports.
- Enjoy the cleanest environment with a convenient and removable cable management design.
- Standard VESA mountable & Accessory Slot design.



1. 5-Way Navi Key
2. HDMI™ 2.0b (WQHD@144Hz)
3. 1x DisplayPort 1.2a
4. Headphone-out
5. AC-in
6. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3PE2CH-017
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	72~216 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	117%/82%
	NTSC (CIE1931 area percentage/overlap)	89%/76%
	sRGB (CIE1976 area percentage/overlap)	135%/97%
	sRGB (CIE1931 area percentage/overlap)	125%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	115%/85%
	Adobe RGB (CIE1931 area percentage/overlap)	93%/78%
	DCI-P3 (CIE1976 area percentage/overlap)	107%/91%
	DCI-P3 (CIE1931 area percentage/overlap)	92%/87%
	Rec.709 (CIE1976 area percentage/overlap)	135%/97%
	Rec.709 (CIE1931 area percentage/overlap)	125%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	78%/75%
	Rec.2020 (CIE1931 area percentage/overlap)	66%/66%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	21
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.49 x 201.01 x 470.61
	Product Dimension without Stand (WxDxH) (mm)	613.49 x 59.56 x 364.46
	Stand Dimension (WxDxH) (mm)	240.5 x 201 x 179.2
	Weight (Net kg)	4.5
	Weight Without Stand (kg)	4.05
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 47.1
	Outer Carton Dimension (WxDxH) (cm)	70.3 x 14.1 x 49.5
	Weight (Gross kg)	6.2
Barcode Info	EAN	4711377381543