

## PATH TO THE FUTURE

Introducing the MSI MAG 32C6X gaming monitor. This cutting-edge monitor features a 32-inch FHD display with a lightning-fast 250Hz(OC) refresh rate and a 1ms MPRT response time. With the MAG 32C6X, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

## SELLING POINTS

- Tấm nền VA - Cung cấp thời gian phản hồi MPRT 1ms, tối ưu màu sắc và độ sáng hiển thị trên màn hình.
- Tốc độ quét hình 250Hz (OC) - Phản hồi nhanh hơn với khung hình mượt mà hơn.
- Thời gian phản hồi 1ms (MPRT) - Loại bỏ hiện tượng xé hình và giật hình.
- AI Vision - Công nghệ AI Vision mới không chỉ có thể hiển thị chi tiết ở vùng tối mà còn tăng cường độ sáng tổng thể và bảo hòa màu sắc.
- Công nghệ Adaptive-Sync - Không bị xé hình, không giật hình, chơi game mượt mà.
- HDR Ready - Hiển thị chi tiết bắt mắt thông qua điều chỉnh độ tương phản và bóng đổ.
- Giảm ánh sáng xanh - Sử dụng giải pháp phần mềm để giảm phát xạ ánh sáng trong vùng xanh tím của quang phổ ánh sáng xanh.



1. 5-Way Joystick Navigator
2. AC-in
3. HDMI™ 2.0b(FHD@240Hz)
4. DisplayPort 1.4a
5. Earphone out
6. Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3DD41M-028
	Color	ID1/Black-Black
Display	Screen Size	31.5" (80.01 cm)
	Active Display Area (mm)	698.4(H) x 392.85(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.36375(H)x0.36375(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~250Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.7~1125 KHz (H) / 48~250 Hz(V)
	Refresh Rate	250Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	85%/78%
	NTSC (CIE1931 area percentage/overlap)	72%/70%
	sRGB (CIE1976 area percentage/overlap)	101%/92%
	sRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/81%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/73%
	DCI-P3 (CIE1976 area percentage/overlap)	78%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/72%
	Rec.709 (CIE1976 area percentage/overlap)	101%/92%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	56%/56%
	Rec.2020 (CIE1931 area percentage/overlap)	53%/53%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	709.4 x 507.2 x 249.8
	Product Dimension without Stand (WxDxH) (mm)	709.4 x 419.1 x 107.2
	Stand Dimension (WxDxH) (mm)	339.8 x 249.8 x 143
	Weight (Net kg)	5.4
	Weight Without Stand (kg)	4.9
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	80 x 17 x 51.4
	Outer Carton Dimension (WxDxH) (cm)	81.8 x 18.8 x 54.9
	Weight (Gross kg)	8.5
Barcode Info	EAN	4711377332682